eurolite®

EUROLITE LED SLS-5 QCL 5x5W Floor 25°

The legendary SLS-5 now with 25° beam angle

Art. No.: 51915382 GTIN: 4026397512601



The article is no longer in our assortment.

Features:

- Equipped with 4in1 quadcolor LEDs for homogeneous light output
- Flat housing form requires minimal space when rigging
- Second mounting bracket for safe standing installation
- Comfortable addressing and setting via control panel with LED display
- Functions: Static colors, RGBW color blend, internal programs, dimmer, strobe, sound-control, sensitivity
- Further display settings: display on or off, display inverted, default settings
- Operable in stand-alone mode or via DMX
- Master/Slave for parallel operation of several devices
- DMX512 control via regular DMX-controller
- Number of DMX channels selectable for numerous applications
- Sound-control via built-in microphone
- Ready for connection with power cord and safety plug
- Feed-through output allows to power up to 8 devices
- Switch-mode power supply for operation between 100 and 240 volts
- Narrow beam angle of 25°
- Control via sound to light via microphone
- Preprogrammed in Light'J; LED PC-Control 512

Logistic

EAN / GTIN: 4026397512601 Weight: 3,35 kg Length: 0.33 m Width: 0.27 m Heigth: 0.18 m

Technical specifications:

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	24 W
IP classification:	IP20

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.

d to light via microphone J; LED PC-Control 512 : 23 cm :: 11 cm t: 27 cm
: 23 cm :: 11 cm
: 11 cm
: 11 cm
t: 27 cm
kâ
XLR
ilt-in microphone
ACL
110 x 270 mm
esigned for household room illumination
effect lighting