

## EUROLITE LED SLS-7 HCL Floor white

Flat LED spotlight with RGBWA+UV color mixing, incl. IR remote control

Art. No.: 51915391

GTIN: 4026397669930



**List price: 129.71 €**

incl. 19% VAT.

### Features:

- Slim design for space-saving applications
- Enjoy perfect solid and pastel colors plus ultra violet thanks to 6-color mixing
- DMX and power terminals intelligently designed for easy wiring
- 7 powerful LEDs 10 W high-power 6in1 HCL RGBWA/UV (homogenous color mix)
- Color blend stepless; color change adjustable; color fade adjustable; Dimmer electronic
- Strobe effect; UV effect
- Integrated show programs
- Direct color selection for 19 preset colors
- The device is cooled by cooling fan
- Control via IR remote control; stand-alone; Sound to light via Microphone; DMX; Master/slave function
- Flicker-free
- With a beam angle of 17°
- With double bracket
- 4 digit 7-segment LED display
- Available in various colors
- Preprogrammed in Light Captain; EASY SHOW 1; LED EASY OPERATOR 4x6; LED EASY OPERATOR DELUXE; Light J; EASY SHOW 2; EASY SHOW 3
- Rubber feet
- Mains input and output for power linking up to 8 units
- Application possibility: Standing; suspended; on stand
- For application areas such as: Clubs/dancing school; Wedding/gala/events; Party room; mobile djs / entertainer; restaurants, bars and hotels

### Package contents

- 1 x light effect, 1 x power cord, 1 x remote control, 1 x battery, 1 x user manual

### Logistic

EAN / GTIN: 4026397669930

Weight: 1,61 kg

Length: 0.25 m

Width: 0.24 m

Height: 0.15 m

## Technical specifications:

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	20 W
IP classification:	IP20
Power connection:	Mains input via IEC connector (M) mounting version power supply cord with safety plug (provided)
Power output:	1 x IEC connector (F) mounting version
Fuse:	T 0,5 A
Lamp type:	LED lamp
LED:	7 x 10 W high-power 6in1 HCL RGBWA/UV (homogenous color mix)
Flash rate:	0 - 20 Hz
DMX channels:	2; 3; 4; 6; 10
DMX input:	3-pin XLR (M) mounting version
DMX output:	3-pin XLR (F) mounting version
Cooling:	Cooling fan
Control:	IR remote control; stand-alone; Sound to light via Microphone; DMX; Master/slave function
Preprogrammed in:	Light Captain; EASY SHOW 1; LED EASY OPERATOR 4x6; LED EASY OPERATOR DELUXE; Light J; EASY SHOW 2; EASY SHOW 3
Projection:	Flicker-free
Beam angle:	17°
Beam angle (1/2 peak):	17°
Housing color:	White
Attachment system:	Double bracket
Display type:	4 digit 7-segment LED display
Transport aid:	Rubber feet
Material:	ABS Acrylonitrile butadiene styrene
Dimensions:	Width: 22 cm Depth: 11 cm Height: 21 cm
Weight:	1,38 kg
Noise classification:	Class 2 (slight noise)
Photobiological safety:	Risk Group 0
Remote control	
Battery:	1 x Button cell 3.0 V CR2025 lithium manganese built-in