

EUROLITE LED SLS-18 TCL/BCL Floor

Slimline LED spot with 3 W 3in1 LED/5 W 2in1 LED

Art. No.: 51915398

GTIN: 4026397446586



The article is no longer in our assortment.

Description:

It is the popular KLS which has paved the path for Slim Line Spots. The KLS was the first successful attempt to replace bulky PAR spots by compact and flat ones - on a bar with 4 spots next to another. As is well known, the concept has been a raving success. As a logic consequence we also transformed the form of single spots - the SLS were born.

Obvious advantages of the SLS: they are slim. Compared to common PAR spots they considerably save space. For this reason they are much more flexible and handy. This is also true for installation, stock ground and transport - for most SLS we sell special cases which are smaller and cheaper than those for PAR spots. In the end, the design can save money.

Meanwhile Eurolite has built up a very rich assortment full of different spots. An assortment which is continuously enlarged. Every delivery finally includes a double bracket enabling an additional use as floor spot. Beside the different sizes of the spots the main differences can be seen in the illuminants. A choice of single LEDs, bicolor, tricolor and quadcolor LEDs is offered.

Features:

- DMX512 control possible via any commercial DMX controller (occupies max.9 channels)
- 5, 6, 7 or 9 DMX channels selectable for numerous applications
- Sound-control via built-in microphone
- Equipped with 3in1 tricolor LEDs (RGB) as well as 2in1 bicolor LEDs (white/amber) for homogeneous light output
- Flat housing form requires minimal space when rigging
- Second mounting bracket for safe standing installation
- Comfortable Addressing and setting via control panel with LCD display and four operating buttons

Logistic

EAN / GTIN: 4026397446586

Weight: 3,98 kg

Length: 0.37 m

Width: 0.18 m

Height: 0.31 m

- Functions: Static colors, RGB color blend, internal programs, dimmer, strobe, sound-control, sensitivity
- Further display settings: display on or off, display inverted, default settings
- Master/Slave for parallel operation of several devices
- Feed-through output allows to power another device
- After every 8 devices the fixtures must have a renewed connection with the power mains
- Locking possibility at the mounting bracket
- Ready for connection via included IEC power cord with safety plug
- Control via sound to light via microphone

Technical specifications:

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	60 W
IP classification:	IP20
Power output:	1 x IEC connector (F) mounting version
Flash rate:	1 - 30 Hz
DMX channels:	6; 5
Control:	Sound to light via microphone
Beam angle (1/2 peak):	40°
Dimensions:	Width: 27 cm Depth: 9,5 cm Height: 31,5 cm
Weight:	3,45 kg
DMX channels:	5/6/7/9
DMX connection:	3-pin XLR
Sound-control:	via built-in microphone
LED type:	3 W TCL / 5 W BCL
LED number:	9 TCLs / 9 BCLs
Beam angle:	40°
Flash-rate:	0-30 Hz
Ventilation fan:	No
Dimensions (W x D x H):	95 x 270 x 315 mm
Legal specifications	
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting