

EUROLITE LED TL-3 RGB+UV Trusslight

Variable truss light and uplight with bright 3 x 7 W RGB+UV LED

Art. No.: 51915445

GTIN: 4026397662078



List price: 101.03 €

incl. 19% VAT.

Description:

Truss light and uplight with bright 3 x 7 W RGB+UV LED

The flicker-free EUROLITE TL-3 Trusslight is equipped with three 7 Watt 4in1 LEDs each in the colors red, green, blue and UV. It is compact and powerful and therefore very suitable for trussing, stand construction and stage mounting. The TL-3 fits perfectly to the 3-point system ALUTRUSS DECOLOCK DQ3.

Also on board are integrated show programs in auto and music mode, direct color selection for 17 colors, dimmer and strobe effect with variably adjustable speed. The trusslight can be used in master/slave mode.

Addressing and settings can be done via the integrated control unit with four-digit LED display. You can control the TL-3 either with the included infrared remote control, in standalone mode, via DMX or optionally QuickDMX.

Thanks to the IEC mains connections, you can easily connect up to eight devices together.

Features:

- Compact and bright
- Perfect for ALUTRUSS 3-POINT SYSTEM DECOLOCK DQ3
- Color change adjustable; Dimmer electronic; color blend stepless
- UV effect; Strobe effect
- 2 integrated show programs
- Direct color selection for 17 preset colors
- Control via IR remote control; stand-alone; DMX; Master/slave function; Sound to light via Microphone; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional)

Logistic

EAN / GTIN: 4026397662078

Weight: 0,99 kg

Length: 0.14 m

Width: 0.14 m

Height: 0.14 m

- Flicker-free
 - With a beam angle of 16°
 - 4 digit 7-segment LED display
 - For application areas such as: Clubs/dancing school; Wedding/gala/events; Stage; mobile djs / entertainer
 - Preprogrammed in LED PC-Control 512; LED EASY OPERATOR DELUXE; Light Captain; EASY SHOW 2; EASY SHOW 3
 - Rubber feet
 - Mains input and output for power linking up to 8 units
 - Very quiet working noise
 - Application possibility: Standing; suspended
- Package contents**
- 1 x spotlight, 1 x power cord, 1 x remote control, 1 x battery, 1 x user manual

Technical specifications:

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	15 W
IP classification:	IP20
Power connection:	Mains input via IEC connector (M) mounting version power supply cord with safety plug (provided)
Power output:	1 x IEC connector (F) mounting version
Fuse:	F 1 A Fuse replaceable
Lamp type:	LED lamp
Flash rate:	1 - 20 Hz
DMX channels:	3; 4; 4; 8
DMX input:	1 x 3-pin XLR (M) mounting version
DMX output:	1 x 3-pin XLR (F) mounting version
Control:	IR remote control; stand-alone; DMX; Master/slave function; Sound to light via Microphone; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional)
Preprogrammed in:	LED PC-Control 512; LED EASY OPERATOR DELUXE; Light Captain; EASY SHOW 2; EASY SHOW 3
Projection:	Flicker-free
Beam angle:	16°
Beam angle (1/2 peak):	16°
Beam angle (1/10 peak):	33°
Housing color:	Black
Attachment system:	M10 thread
Display type:	4 digit 7-segment LED display
Transport aid:	Rubber feet
Material:	Metal
Dimensions:	Width: 12,2 cm Depth: 10,8 cm Height: 11,7 cm
Weight:	890 g
Noise classification:	Class 1 (very slight noise, suitable for noise-sensitive environments)

Photobiological safety:	Risk Group 0
Power cord	
Cable construction:	3 x 0,75 mm ² H05VV-F
Cable length:	Approx. 1,1 m
Remote control	
Battery:	1 x Button cell 3.0 V CR2025 lithium manganese built-in
Legal specifications	
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting