

EUROLITE LED PST-30 3000K Spot

Narrow beam pinspot with 30 W warm white (WW) LED

Art. No.: 51916115

GTIN: 4026397751666



Features:

- For illuminating e.g. mirror balls, entrance or counter areas or as basic illumination
- 1 LED 30 W warm white (WW)
- Focus manual
- Spot effect
- Gobo wheel with static gobos, 4 reduction gobos
- The device is cooled by passive convection cooling
- Control via plug and play
- Flicker-free
- With a beam angle of 8°
- Very high color rendering index (CRI)
- With mounting bracket
- For application areas such as: Clubs/dancing school; wedding/gala/events; Trade fair and shop fitting; installation; restaurants, bars and hotels
- Silent operation
- Application possibility: Suspended; on stand

Logistic

EAN / GTIN: 4026397751666

Weight: 1,14 kg

Length: 0.33 m

Width: 0.13 m

Height: 0.12 m

Technical specifications:

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	30 W
Protection class:	Protection class I
Power connection:	Fixed power supply cord with safety plug
Cable construction:	3 x 0.75 mm ² H05VV-F

Lamp type:	LED lamp
LED type:	1 x 30 W warm white (WW)
Equipment:	Focus manual
Gobos:	Gobo wheel with static gobos, 4 reduction gobos
Cooling:	Passive convection cooling
Control:	Plug and play
Projection:	Flicker-free
Beam angle:	8°
Beam angle (1/2 peak):	8° 11° 14° 16°
Beam angle (1/10 peak):	8° 11° 14° 16°
Color rendering index (CRI):	97 Ra
Illuminance in Lux (lx):	Warm white (WW) 1m: 6762 lx, 3m: 754 lx, 6m: 191 lx
Luminous flux:	3000 lm
Housing color:	Black matte
Attachment system:	Mounting bracket
Material:	Aluminum casting
Dimensions:	Length: 27.5 cm Width: 10.5 cm Height: 14.5 cm
Weight:	1.00 kg
Noise classification:	Class 0 (no noise at all)
Diameter mounting holes:	1 x Ø10mm
Material:	Metal

Scope of delivery:

1 x spotlight
1 x key
1 x user manual