

EUROLITE LED PST-10 QCL Spot wh

LED pinspot with COB LED and DMX control as well as IR remote control

Art. No.: 51916153

GTIN: 4026397703184



List price: 117.81 €

incl. 19% VAT.

Features:

- Additional frost filter provides a wide, soft and homogeneous light
- 1 powerful LED 10 W COB (chip-on-board) 4in1 QCL RGBW (homogenous color mix)
- Direct color selection for 19 preset colors
- The device is cooled by passive convection cooling
- Control via IR remote control; stand-alone; DMX; sound to light via microphone; master/slave function
- Flicker-free
- With a beam angle of 4°
- 4 digit 7-segment LED display
- Color blend stepless; color change adjustable; color fade adjustable; Dimmer electronic
- Strobe effect
- Preprogrammed in Light Captain; Colorchief
- With double bracket
- For application areas such as: Clubs/dancing school; party room; mobile djs / entertainer; restaurants, bars and hotels
- Silent operation
- Application possibility: Standing; suspended; on stand

Package contents

- 1 x device, 1 x user manual, 2 x mounting bracket, 1 x frost filter, 1 x lamp clamping ring, 1 x remote control, 1 x battery

Logistic

EAN / GTIN: 4026397703184

Weight: 1,20 kg

Length: 0.15 m

Width: 0.15 m

Height: 0.29 m

Technical specifications:

Power supply: 100-240 V AC, 50/60 Hz

Power consumption:	12 W
IP classification:	IP20
Protection class:	Protection class II
Power connection:	Fixed power supply cord with Euro plug
Cable length:	Approx. 1 m
Fuse:	T 0,5 A fuse replaceable
Lamp type:	LED lamp
LED type:	1 x 10 W COB (chip-on-board) 4in1 QCL RGBW (homogenous color mix)
Flash rate:	0 - 20 Hz
DMX channels:	3; 4; 5; 6; 9
Cooling:	Passive convection cooling
Control:	IR remote control; stand-alone; DMX; sound to light via microphone; master/slave function
Preprogrammed in:	Light Captain; Colorchief
Projection:	Flicker-free
Beam angle:	4°
Beam angle (1/2 peak):	4° Frost filter 16°
Beam angle (1/10 peak):	7° Frost filter 36°
Housing color:	White
Attachment system:	Double bracket
Display type:	4 digit 7-segment LED display
Dimensions:	Length: 20,2 cm Width: 16,3 cm Height: 20,3 cm
Weight:	1,03 kg
Noise classification:	Class 0 (no noise at all)
Photobiological safety:	Risk Group 0
Frost filter	
Material:	Plastic, 1 mm
Dimensions:	Diameter: Ø 7,7 cm
Remote control	
Battery:	1 x button cell 3.0 V CR2025 lithium manganese built-in
Legal specifications	
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting