

EUROLITE LED Z-PAR RGBW 4x10W

Zoom spot with 4 x 10 W 4in1 LED (RGBW), beam angle from 6-49°

Art. No.: 51916501

GTIN: 4026397605853



The article is no longer in our assortment.

Description:

Zoom spotlight with a beam angle of 6-49°.

The zoom spotlight EUROLITE LED Z-PAR is equipped with four 10 Watt LEDs in red, green, blue and white. You can use the spotlight on stages, in discotheques and also in theatres. The spotlight scores with its motorized zoom with a beam angle of 6° to 29°.

The flicker-free EUROLITE LED Z-PAR with RGBW color mixing offers you a master/slave mode for control, but you can also control the music via the built-in microphone and call up internal programs. An infrared remote control is included in the scope of delivery.

Addressing and setting can be carried out conveniently via the Control Board with LED display and four control buttons. You can also set the microphone sensitivity via the Control Board.

The zoom spotlight is supplied ready for connection to you via the supplied power cord with safety plug.

Features:

- 4 powerful LEDs 10 W high-power 4in1 QCL RGBW (homogenous color mix)
- Zoom motor driven
- Color change adjustable; Dimmer electronic; color blend stepless
- Strobe effect
- 3 integrated show programs
- Direct color selection for 15 preset colors
- The device is cooled by low-noise cooling fan
- Control via stand-alone; DMX; IR remote control; sound to light via microphone
- Flicker-free

Logistic

EAN / GTIN: 4026397605853

Weight: 2,50 kg

Length: 0.35 m

Width: 0.21 m

Height: 0.18 m

- With a beam angle of 6° - 49°
 - With double bracket
 - 4 digit 7-segment LED display
 - Preprogrammed in Light´J; LED PC-Control 512; Light Captain
 - For application areas such as: Clubs/dancing school; wedding/gala/events; mobile djs / entertainer
 - Application possibility: Suspended; on stand
- Package contents**
- 1 x spotlight, 1 x user manual, 1 x power cord, 1 x remote control, 1 x battery

Technical specifications:

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	35 W
IP classification:	IP20
Power connection:	Mains input via IEC connector (M) mounting version power supply cord with safety plug (provided)
Power output:	1 x IEC connector (F) mounting version
Lamp type:	LED lamp
LED type:	4 x 10 W high-power 4in1 QCL RGBW (homogenous color mix)
Equipment:	Zoom motor driven
DMX channels:	4; 9
DMX input:	1 x 3-pin XLR (M) mounting version
DMX output:	1 x 3-pin XLR (F) mounting version
Cooling:	Low-noise cooling fan
Control:	Stand-alone; DMX; IR remote control; sound to light via microphone
Preprogrammed in:	Light´J; LED PC-Control 512; Light Captain
Projection:	Flicker-free
Beam angle:	6° - 49°
Beam angle (1/2 peak):	6 - 29°
Beam angle (1/10 peak):	10 - 49°
Housing color:	Black
Attachment system:	Double bracket
Display type:	4 digit 7-segment LED display
Material:	Aluminum
Dimensions:	Width: 18 cm Depth: 27,5 cm Height: 25 cm
Weight:	2,20 kg
Noise classification:	Class 2 (slight noise)
Remote control	
Battery:	1 x button cell 3.0 V CR2025 lithium manganese built-in
Legal specifications	
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting