# eurolite®

## EUROLITE LED Z-4000 Beam Effect

Extremely bright derby with 3 W LED in 8 colors, incl. IR remote control

Art. No.: 51918223 GTIN: 4026397699760









## List price: 201.11 €

incl. 19% VAT.

#### Features:

- Absolute eyecatcher
- 8 powerful LEDs 3 W SMD 3535 R/G/B/W/A/C/Y/P
- Multi beam effect
- 4 integrated show programs
- Direct color selection for 25 preset colors
- The device is cooled by low-noise cooling fan
- Control via stand-alone; IR remote control; DMX; master/slave function; sound to light via microphone; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional)
- With a beam angle of 100°
- With mounting bracket
- 4 digit 7-segment LED display
- Dimmer electronic; Rotation speed stepless
- Preprogrammed in Light Captain; EASY SHOW 2
- For application areas such as: Clubs/dancing school; party room; mobile djs / entertainer; small rental
- Application possibility: Suspended; on stand Package contents
- 1 x light effect, 1 x user manual, 1 x power cord, 1 x remote control, 1 x battery

| Technical specifications: |                        |
|---------------------------|------------------------|
| Power supply:             | 100-240 V AC, 50/60 Hz |
| Power consumption:        | 35 W                   |

### Logistic

EAN / GTIN: 4026397699760 Weight: 3,20 kg Length: 0.32 m Width: 0.32 m Heigth: 0.36 m

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.

| Protection class: Power connection: Fuse: LED type: Flash rate: DMX channels: | Protection class I<br>Mains input via IEC connector (M) mounting<br>version power supply cord with safety plug<br>(provided)<br>T 1 A fuse replaceable<br>8 x 3 W SMD 3535 R/G/B/W/A/C/Y/P<br>0 - 20 Hz                   |
|---|---|
| Fuse:<br>LED type:<br>Flash rate:   | version power supply cord with safety plug<br>(provided)<br>T 1 A fuse replaceable<br>8 x 3 W SMD 3535 R/G/B/W/A/C/Y/P<br>0 - 20 Hz   |
| LED type:<br>Flash rate:  | 8 x 3 W SMD 3535 R/G/B/W/A/C/Y/P<br>0 - 20 Hz   |
| Flash rate:   | 0 - 20 Hz   |
|   |   |
| DMX channels:   | 5.10  |
|   | 5; 12   |
| DMX input:  | 3-pin XLR (M) mounting version  |
| DMX output:   | 3-pin XLR (F) mounting version  |
| Cooling:  | Low-noise cooling fan   |
| Control:  | Stand-alone; IR remote control; DMX;<br>master/slave function; sound to light via<br>microphone; QuickDMX via USB (optional); W-<br>DMX by wireless solution via USB (optional);<br>CRMX by LumenRadio via USB (optional) |
| Preprogrammed in:   | Light Captain; EASY SHOW 2  |
| Beam angle:   | 100°  |
| Beam angle (1/2 peak):  | 100°  |
| Housing color:  | Black   |
| Attachment system:  | Mounting bracket  |
| Display type:   | 4 digit 7-segment LED display   |
| Dimensions:   | Width: 28,2 cm<br>Depth: 32,0 cm<br>Height: 28,2 cm   |
| Weight:   | 2,60 kg   |
| Noise classification:   | Class 3 (clearly perceptible sounds)  |
| Remote control  |   |
| Battery:  | 1 x button cell 3.0 V CR2025 lithium manganese built-in   |
| Legal specifications  |   |
| Special product:  | Not designed for household room illumination  |
| Intended use:   | Show effect lighting  |