eurolite®

EUROLITE LED DMF-5 Hybrid Flower Effect

Effect spotlight with flower and blacklight effect, incl. IR remote control

Art. No.: 51918564 GTIN: 4026397699777









List price: 117.81 €

incl. 19% VAT.

Features:

- 2 disco balls fill the room with innumerable colorful beams
- 12 powerful LEDs 3 W R/G/B/W/A/P
- 8 powerful LEDs 3 W ultra violet (UV)
- Flower effect; UV effect
- 3 integrated show programs
- Direct color selection for 20 preset colors
- The device is cooled by passive convection cooling
- Control via stand-alone; IR remote control; DMX; master/slave function; sound to light via microphone; QuickDMX (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional)
- Preprogrammed in Light Captain; Light J
- Flicker-free
- With a beam angle of 120°
- 4 digit 7-segment LED display
- For application areas such as: Clubs/dancing school; party room
- Silent operation
- Application possibility: Suspended; on stand
- Package contents
- 1 x light effect, 1 x user manual, 1 x power cord, 1 x remote control, 1 x battery

Technical specifications:	
Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	24 W

Logistic

EAN / GTIN: 4026397699777 Weight: 1,83 kg Length: 0.38 m Width: 0.17 m Heigth: 0.14 m

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.

IP classification:	IP20
Protection class:	Protection class I
Power connection:	Mains input via IEC connector (M) mounting version power supply cord with safety plug (provided)
Power output:	IEC connector (F) mounting version
Fuse:	5 x 20 mm, T 0,5 A fuse replaceable
Lamp type:	LED lamp
LED type:	12 x 3 W R/G/B/W/A/P 8 x 3 W ultra violet (UV)
DMX channels:	6; 11
DMX input:	3-pin XLR (M) mounting version
DMX output:	3-pin XLR (F) mounting version
Cooling:	Passive convection cooling
Control:	Stand-alone; IR remote control; DMX; master/slave function; sound to light via microphone; QuickDMX (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional)
Preprogrammed in:	Light Captain; Light J
Projection:	Flicker-free
Beam angle:	120°
Beam angle (1/2 peak):	Multi beam effect 120°
Housing color:	Black
Display type:	4 digit 7-segment LED display
Dimensions:	Width: 36,0 cm Depth: 9,0 cm Height: 15,0 cm
Weight:	1,60 kg
Noise classification:	Class 0 (no noise at all)
Remote control	
Battery:	1 x button cell 3.0 V CR2025 lithium manganese built-in
Legal specifications	
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting