# eurolite®

## **EUROLITE LED GF-120 Flower Effect**

LED flower effect with cold white 120 W COB LED and gobo wheel

Art. No.: 51918589 GTIN: 4026397714616







## List price: 296.31 €

incl. 19% VAT.

#### Features:

- Heart gobo for romantic occasions
- Flower mirror multiplies the gobos and lets them dance in the room
- 1 powerful LED 120 W COB (chip-on-board) cold white (CW)
- Gobo wheel with static gobos, 11 color gobos and open<BR>rainbow effect with adjustable speed in both directions
- 16 integrated show programs
- The device is cooled by cooling fan
- Control via stand-alone; sound to light via microphone; DMX; master/slave function; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional)
- Flicker-free
- Gobo effect; flower effect; strobe effect
- With a beam angle of 50°
- With mounting bracket
- Multicolor TFT display
- Dimmer electronic
- Preprogrammed in Light'J; Light Captain; LED PC-Control 512; Colorchief
- For application areas such as: Clubs/dancing school; party room; mobile djs / entertainer; restaurants, bars and hotels
- Application possibility: Suspended; on stand

#### Package contents

- 1 x light effect, 1 x power cord, 1 x user manual

#### Logistic

EAN / GTIN: 4026397714616 Weight: 4,50 kg Length: 0.37 m Width: 0.27 m Heigth: 0.20 m

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.

### Technical specifications:

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	65 W
IP classification:	IP20
Protection class:	Protection class I
Power connection:	Mains input via IEC connector (M) mounting version power supply cord with safety plug (provided)
Fuse:	5 x 20 mm, T 1 A fuse replaceable
Lamp type:	LED lamp
LED type:	1 x 120 W COB (chip-on-board) cold white (CW)
Flash rate:	0 - 25 Hz
Gobos:	Gobo wheel with static gobos, 11 color gobos and open
	Rainbow effect with adjustable speed in both directions
DMX channels:	6
Cooling:	Cooling fan
Control:	Stand-alone; sound to light via microphone; DMX; master/slave function; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional)
Preprogrammed in:	Light´J; Light Captain; LED PC-Control 512; Colorchief
Projection:	Flicker-free
Beam angle:	50°
Beam angle (1/2 peak):	50°
Housing color:	Black
Attachment system:	Mounting bracket
Display type:	Multicolor TFT display
Material:	Metal
Dimensions:	Width: 32,0 cm
	Depth: 22,0 cm
	Height: 19,0 cm
Weight:	4,11 kg
Mounting bracket	
Diameter mounting holes:	1 x Ø13mm
Material:	Metal, 3 mm
Power cord	
Cable construction:	3 x 0,75 mm² H05VV-F
Cable length:	Approx. 1 m
Legal specifications	
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting