eurolite®

EUROLITE LED CAT-80 Beam Effect

LED beam effect with cold white 80 W COB LED and gobo wheel

Art. No.: 51918595 GTIN: 4026397713398











List price: 379.61 €

incl. 19% VAT.

Features:

- 3 different motion axes
- Rotating faceted mirror inside
- Rotating and swiveling mirror cylinder
- Generates countless moving patterns in the room
- 1 powerful LED 80 W COB (chip-on-board) cold white (CW)
- Gobo wheel with static gobos; focus manual
- Dimmer electronic
- Mirror cylinder effect; strobe effect
- Gobo wheel with static gobos, 9 color gobos and open
- The device is cooled by cooling fan
- Control via stand-alone; master/slave function; sound to light via microphone; DMX; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional)
- Preprogrammed in Light J; Light Captain; EASY SHOW 2; EASY SHOW 3; Colorchief
- Flicker-free
- OLED display
- For application areas such as: Clubs/dancing school; party room; stage; mobile djs / entertainer; rental
- Application possibility: Suspended; on stand Package contents
- 1 x light effect, 1 x user manual, 1 x power cord, 1 x XLR cable

Logistic

EAN / GTIN: 4026397713398 Weight: 4,00 kg Length: 0.39 m Width: 0.35 m Heigth: 0.24 m

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.

Technical specifications:

| · | |
|-----------------------|---|
| Power supply: | 100-240 V AC, 50/60 Hz |
| Power consumption: | 110 W |
| IP classification: | IP20 |
| Protection class: | Protection class I |
| Power connection: | Mains input via P-Con (blue), mounting version power supply cord with safety plug |
| Fuse: | 5 x 20 mm, T 2 A fuse replaceable |
| Lamp type: | LED lamp |
| LED type: | 1 x 80 W COB (chip-on-board) cold white (CW) |
| Flash rate: | 0 - 25 Hz |
| Equipment: | Gobo wheel with static gobos; focus manual |
| Gobos: | Gobo wheel with static gobos, 9 color gobos and open |
| DMX channels: | 7 |
| DMX input: | 3-pin XLR (M) mounting version |
| DMX output: | 3-pin XLR (F) mounting version |
| Cooling: | Cooling fan |
| Control: | Stand-alone; master/slave function; sound to light via microphone; DMX; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional) |
| Preprogrammed in: | Light J; Light Captain; EASY SHOW 2; EASY SHOW 3; Colorchief |
| Projection: | Flicker-free |
| Housing color: | Black |
| Display type: | OLED display |
| Dimensions: | Width: 29,0 cm Depth: 18,5 cm Height: 31,5 cm |
| Weight: | 3,08 kg |
| Noise classification: | Class 3 (clearly perceptible sounds) |
| Legal specifications | |
| Special product: | Not designed for household room illumination |
| Intended use: | Show effect lighting |