eurolite®

EUROLITE LED SCY-50 Hybrid Beam Effect

LED spotlight with twofold effects: 6in1 HCL RGBWA/UV LEDs, dynamic color effects and strobe

Art. No.: 51918672 GTIN: 4026397632927

000







The article is no longer in our assortment.

Features:

- Individual control of all RGBAW+UV and RGB LEDs for use as blacklight, ambient light, stroboscope or PAR spotlight
- 5 powerful LEDs 10 W high-power 6in1 HCL RGBWA/UV (homogenous color mix)
- 50 powerful LEDs 0,2 W SMD 5050 3in1 TCL RGB (homogenous color mix)
- Fan effect; strobe effect; UV effect
- Integrated show programs
- Direct color selection for 25 preset colors
- The device is cooled by cooling fan
- Control via stand-alone; IR remote control; DMX; master/slave function; sound to light
- Preprogrammed in LED PC-Control 512; Light Captain
- With a beam angle of 5°
- With mounting bracket
- For application areas such as: Clubs/dancing school; party room; restaurants, bars and hotels
- Application possibility: Suspended; on stand Package contents
- 1 x light effect, 1 x user manual, 1 x power cord, 1 x remote control, 1 x battery

Technical specifications:

| Power supply: | 100-240 V AC, 50/60 Hz |
|--------------------|------------------------|
| Power consumption: | 50 W |
| IP classification: | IP20 |

Logistic

EAN / GTIN: 4026397632927 Weight: 3,50 kg Length: 0.47 m Width: 0.28 m Heigth: 0.21 m

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.

| Power connection: | Mains input via IEC connector (M) mounting version power supply cord with safety plug (provided) |
|-------------------------|---|
| Power output: | 1 x IEC connector (F) mounting version |
| Lamp type: | LED lamp |
| LED type: | 5 x 10 W high-power 6in1 HCL RGBWA/UV (homogenous color mix) 50 x 0,2 W SMD 5050 3in1 TCL RGB |
| | (homogenous color mix) |
| Flash rate: | 0 - 20 Hz |
| DMX channels: | 1; 6; 15 |
| DMX input: | 3-pin XLR (M) mounting version |
| DMX output: | 3-pin XLR (F) mounting version |
| Cooling: | Cooling fan |
| Control: | Stand-alone; IR remote control; DMX; master/slave function; sound to light |
| Preprogrammed in: | LED PC-Control 512; Light Captain |
| Beam angle: | 5° |
| Beam angle (1/2 peak): | 5° |
| Housing color: | Black |
| Attachment system: | Mounting bracket |
| Dimensions: | Width: 41,8 cm Depth: 23 cm Height: 17,8 cm |
| Weight: | 3,00 kg |
| Noise classification: | Class 2 (slight noise) |
| Photobiological safety: | Risk Group 0 |
| Remote control | |
| Battery: | 1 x button cell 3.0 V CR2025 lithium manganese built-in |
| Legal specifications | |
| Special product: | Not designed for household room illumination |
| Intended use: | Show effect lighting |
| | |