eurolite®

EUROLITE LED PR-100/32 Pixel DMX rail bk

DMX controlled pixel tube with RGB color mixing

Art. No.: 51928608 GTIN: 4026397684544



List price: 236.81 €

incl. 19% VAT.

Features:

- DMX and power terminals intelligently designed for easy wiring
- Front cover: black
- 96 powerful LEDs SMD 5050 3in1 TCL RGB (homogenous color mix)
32 segments controlled separately
- Color blend stepless; color change adjustable; colors preset; Dimmer electronic
- 12 integrated show programs
- Direct color selection for 17 preset colors
- The device is cooled by passive convection cooling
- Control via stand-alone; DMX; sound to light via microphone
- With a beam angle of 120°
- With mounting bracket
- 4 digit 7-segment LED display
- Silent operation
- Preprogrammed in Light Captain
- Mains input and output for power linking up to 8 units
- For application areas such as: Clubs/dancing school; Trade fair and shop fitting; stage; restaurants, bars and hotels
- Application possibility: Suspended; wall mounting Package contents
- 1 x light effect, 1 x user manual, 1 x power cord

Technical specifications:

Power supply:

100-240 V AC, 50/60 Hz

Logistic

EAN / GTIN: 4026397684544 Weight: 2,55 kg Length: 1.04 m Width: 0.10 m Heigth: 0.20 m

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.

IP classification: IP20 Protection class: Protection class I Power connection: Mains input via P-Con (blue), mounting version power supply cord with safety plug (provided) Power output: 1 x P-Con (gray), mounting version Lamp type: LED lamp LED type: 96 x SMD 5050 3in1 TCL RGB (homogenous color mix) Flash rate: 0,25 - 10 Hz DMX channels: 3; 5; 8; 48; 96 DMX input: 3-pin XLR (M) mounting version DMX output: 3-pin XLR (F) mounting version Cooling: Passive convection cooling Control: Stand-alone; DMX; sound to light via microphone Preprogrammed in: Light Captain Beam angle: 120° Beam angle (1/2 peak): 120° Housing color: Black Attachment system: Mounting bracket Display type: 4 digit 7-segment LED display Dimensions: Length: 99,9 cm Weight: 2,01 kg Noise classification: Class 0 (no noise at all) Legal specifications Special product: Special product: Not designed for household room illumination <	Power consumption:	30 W
Power connection: Mains input via P-Con (blue), mounting version power supply cord with safety plug (provided) Power output: 1 x P-Con (gray), mounting version Lamp type: LED lamp LED type: 96 x SMD 5050 3in1 TCL RGB (homogenous color mix) Flash rate: 0,25 - 10 Hz DMX channels: 3; 5; 8; 48; 96 DMX input: 3-pin XLR (M) mounting version DMX output: 3-pin XLR (F) mounting version Cooling: Passive convection cooling Control: Stand-alone; DMX; sound to light via microphone Preprogrammed in: Light Captain Beam angle: 120° Housing color: Black Attachment system: Mounting bracket Display type: 4 digit 7-segment LED display Dimensions: Length: 99,9 cm Weight: 2,01 kg Noise classification: Class 0 (no noise at all) Legal specifications Special product: Special product: Not designed for household room illumination	IP classification:	IP20
power supply cord with safety plug (provided) Power output: 1 x P-Con (gray), mounting version Lamp type: LED lamp LED type: 96 x SMD 5050 3in1 TCL RGB (homogenous color mix) Flash rate: 0,25 - 10 Hz DMX channels: 3; 5; 8; 48; 96 DMX input: 3-pin XLR (M) mounting version DMX output: 3-pin XLR (F) mounting version Cooling: Passive convection cooling Control: Stand-alone; DMX; sound to light via microphone Preprogrammed in: Light Captain Beam angle: 120° Beam angle: 120° Housing color: Black Attachment system: Mounting bracket Display type: 4 digit 7-segment LED display Dimensions: Length: 99,9 cm Weight: 2,01 kg Noise classification: Class 0 (no noise at all) Legal specifications Special product:	Protection class:	Protection class I
Lamp type: LED lamp LED type: 96 x SMD 5050 3in1 TCL RGB (homogenous color mix) Flash rate: 0,25 - 10 Hz DMX channels: 3; 5; 8; 48; 96 DMX input: 3-pin XLR (M) mounting version DMX output: 3-pin XLR (F) mounting version Cooling: Passive convection cooling Control: Stand-alone; DMX; sound to light via microphone Preprogrammed in: Light Captain Beam angle: 120° Housing color: Black Attachment system: Mounting bracket Display type: 4 digit 7-segment LED display Dimensions: Length: 99,9 cm Weight: 2,01 kg Noise classification: Class 0 (no noise at all) Legal specifications Special product:	Power connection:	
LED type: 96 x SMD 5050 3in1 TCL RGB (homogenous color mix) Flash rate: 0,25 - 10 Hz DMX channels: 3; 5; 8; 48; 96 DMX input: 3-pin XLR (M) mounting version DMX output: 3-pin XLR (F) mounting version Cooling: Passive convection cooling Control: Stand-alone; DMX; sound to light via microphone Preprogrammed in: Light Captain Beam angle: 120° Housing color: Black Attachment system: Mounting bracket Display type: 4 digit 7-segment LED display Dimensions: Length: 99,9 cm Weight: 2,01 kg Noise classification: Class 0 (no noise at all) Legal specifications Special product:	Power output:	1 x P-Con (gray), mounting version
color mix)Flash rate:0,25 - 10 HzDMX channels:3; 5; 8; 48; 96DMX input:3-pin XLR (M) mounting versionDMX output:3-pin XLR (F) mounting versionCooling:Passive convection coolingControl:Stand-alone; DMX; sound to light via microphonePreprogrammed in:Light CaptainBeam angle:120°Housing color:BlackAttachment system:Mounting bracketDisplay type:4 digit 7-segment LED displayDimensions:Length: 99, 9 cm Width: 5,95 cm Height: 13,2 cmWeight:2,01 kgNoise classification:Class 0 (no noise at all)Legal specificationsSpecial product:Special product:Not designed for household room illumination	Lamp type:	LED lamp
DMX channels: 3; 5; 8; 48; 96 DMX input: 3-pin XLR (M) mounting version DMX output: 3-pin XLR (F) mounting version Cooling: Passive convection cooling Control: Stand-alone; DMX; sound to light via microphone Preprogrammed in: Light Captain Beam angle: 120° Housing color: Black Attachment system: Mounting bracket Display type: 4 digit 7-segment LED display Dimensions: Length: 99,9 cm Weight: 2,01 kg Noise classification: Class 0 (no noise at all) Legal specifications Special product:	LED type:	· · ·
DMX input: 3-pin XLR (M) mounting version DMX output: 3-pin XLR (F) mounting version Cooling: Passive convection cooling Control: Stand-alone; DMX; sound to light via microphone Preprogrammed in: Light Captain Beam angle: 120° Housing color: Black Attachment system: Mounting bracket Display type: 4 digit 7-segment LED display Dimensions: Length: 99,9 cm Weight: 2,01 kg Noise classification: Class 0 (no noise at all) Legal specifications Special product:	Flash rate:	0,25 - 10 Hz
DMX output: 3-pin XLR (F) mounting version Cooling: Passive convection cooling Control: Stand-alone; DMX; sound to light via microphone Preprogrammed in: Light Captain Beam angle: 120° Beam angle (1/2 peak): 120° Housing color: Black Attachment system: Mounting bracket Display type: 4 digit 7-segment LED display Dimensions: Length: 99,9 cm Width: 5,95 cm Height: 13,2 cm Weight: 2,01 kg Noise classification: Class 0 (no noise at all) Legal specifications Special product:	DMX channels:	3; 5; 8; 48; 96
Cooling: Passive convection cooling Control: Stand-alone; DMX; sound to light via microphone Preprogrammed in: Light Captain Beam angle: 120° Beam angle (1/2 peak): 120° Housing color: Black Attachment system: Mounting bracket Display type: 4 digit 7-segment LED display Dimensions: Length: 99,9 cm Width: 5,95 cm Height: 13,2 cm Weight: 2,01 kg Noise classification: Class 0 (no noise at all) Legal specifications Special product:	DMX input:	3-pin XLR (M) mounting version
Control: Stand-alone; DMX; sound to light via microphone Preprogrammed in: Light Captain Beam angle: 120° Beam angle (1/2 peak): 120° Housing color: Black Attachment system: Mounting bracket Display type: 4 digit 7-segment LED display Dimensions: Length: 99,9 cm Width: 5,95 cm Height: 13,2 cm Weight: 2,01 kg Noise classification: Class 0 (no noise at all) Legal specifications Special product:	DMX output:	3-pin XLR (F) mounting version
Preprogrammed in: Light Captain Beam angle: 120° Beam angle (1/2 peak): 120° Housing color: Black Attachment system: Mounting bracket Display type: 4 digit 7-segment LED display Dimensions: Length: 99,9 cm Width: 5,95 cm Height: 13,2 cm Weight: 2,01 kg Noise classification: Class 0 (no noise at all) Legal specifications Special product:	Cooling:	Passive convection cooling
Beam angle: 120° Beam angle (1/2 peak): 120° Housing color: Black Attachment system: Mounting bracket Display type: 4 digit 7-segment LED display Dimensions: Length: 99,9 cm Width: 5,95 cm Height: 13,2 cm Weight: 2,01 kg Noise classification: Class 0 (no noise at all) Legal specifications Special product:	Control:	Stand-alone; DMX; sound to light via microphone
Beam angle (1/2 peak): 120° Housing color: Black Attachment system: Mounting bracket Display type: 4 digit 7-segment LED display Dimensions: Length: 99,9 cm Width: 5,95 cm Height: 13,2 cm Weight: 2,01 kg Noise classification: Class 0 (no noise at all) Legal specifications Special product:	Preprogrammed in:	Light Captain
Housing color: Black Attachment system: Mounting bracket Display type: 4 digit 7-segment LED display Dimensions: Length: 99,9 cm Width: 5,95 cm Height: 13,2 cm Weight: 2,01 kg Noise classification: Class 0 (no noise at all) Legal specifications Special product:	Beam angle:	120°
Attachment system: Mounting bracket Display type: 4 digit 7-segment LED display Dimensions: Length: 99,9 cm Width: 5,95 cm Height: 13,2 cm Weight: 2,01 kg Noise classification: Class 0 (no noise at all) Legal specifications Special product:	Beam angle (1/2 peak):	120°
Display type: 4 digit 7-segment LED display Dimensions: Length: 99,9 cm Width: 5,95 cm Width: 13,2 cm Weight: 2,01 kg Noise classification: Class 0 (no noise at all) Legal specifications Special product: Not designed for household room illumination	Housing color:	Black
Dimensions: Length: 99,9 cm Width: 5,95 cm Height: 13,2 cm Weight: 2,01 kg Noise classification: Class 0 (no noise at all) Legal specifications Special product:	Attachment system:	Mounting bracket
Width: 5,95 cm Height: 13,2 cm Weight: 2,01 kg Noise classification: Class 0 (no noise at all) Legal specifications Special product: Not designed for household room illumination	Display type:	4 digit 7-segment LED display
Height: 13,2 cm Weight: 2,01 kg Noise classification: Class 0 (no noise at all) Legal specifications Special product: Not designed for household room illumination	Dimensions:	Length: 99,9 cm
Weight: 2,01 kg Noise classification: Class 0 (no noise at all) Legal specifications Special product: Not designed for household room illumination		
Noise classification: Class 0 (no noise at all) Legal specifications Special product: Not designed for household room illumination		Height: 13,2 cm
Legal specifications Special product: Not designed for household room illumination	Weight:	2,01 kg
Special product: Not designed for household room illumination	Noise classification:	Class 0 (no noise at all)
	Legal specifications	
Intended use: Show effect lighting	Special product:	Not designed for household room illumination
	Intended use:	Show effect lighting