

EUROLITE LED Pixel Ball PSU-5 ArtNet/DMX MK2

Control unit for EUROLITE LED Pixel Ball 360° 1m MK2

Art. No.: 51928765

GTIN: 4026397746273

The article is no longer in our assortment.

Features:

- Control via stand-alone; DMX; QuickDMX via USB (optional); Art-Net; master/slave function; W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional); RDM
- DMX fail mode (hold; blackout)
- Monochrome OLED display
- Mains input and output for power linking up to 8 units
- Built with SEETRONIC connector
- Interface
- For application areas such as: Clubs/dancing school; wedding/gala/events; installation; restaurants, bars and hotels
- Silent operation
- Application possibility: Suspended; wall mounting
- 30 integrated show programs
- The device is cooled by passive convection cooling

Package contents

- 1 x device, 1 x user manual, 1 x power cord

Logistic

EAN / GTIN: 4026397746273

Technical specifications:

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	130 W
Protection class:	Protection class I
Power connection:	Mains input via P-Con (blue), mounting version power supply cord with safety plug

Cable construction:	3 x 1,0 mm² H05VV-F
Power output:	P-Con (gray), mounting version
Fuse:	5 x 20 mm, T 1 A fuse replaceable
DMX channels:	3; 5; 7; 10; 15; 19
DMX input:	3-pin XLR (M) mounting version 5-pin XLR (M) mounting version
DMX output:	3-pin XLR (F) mounting version 5-pin XLR (F) mounting version
Network connection:	Protocol: Art-Net 3 via 2x RJ-45 E-Con (F) mounting version
Cooling:	Passive convection cooling
Control:	Stand-alone; DMX; QuickDMX via USB (optional); Art-Net; master/slave function; W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional); RDM
DMX fail mode:	Hold; blackout
Housing color:	Black
Display type:	Monochrome OLED display
USB port:	Type A
Use of brands:	Built with SEETRONIC connector
Material:	Metal
Housing design:	Interface
Dimensions:	Length: 100 cm Depth: 7,7 cm Height: 10,7 cm
Weight:	3,6 kg
Noise classification:	Class 0 (no noise at all)