# EUROLITE LED PIX-24 RGB 24x3W Bar

LED bar with 30° beam angle

eurolite









## The article is no longer in our assortment.

#### Features:

- Equipped with 24 x 3 W LEDs (red: 8, green: 8, blue: 8) distributed in 8 segments
- Operable in stand-alone mode or via DMX
- DMX512 control possible via any commercial DMX controller
- 6, 9, 15, 24, 27 DMX channels selectable for various applications
- Sound-control via built-in microphone
- Functions: static colors; automatic color change, 14 built-in programs and strobe effect with variable speed; Master/Slave
- On-board control board with 2 x 8-digit LC-display
- Locking possibility at the mounting bracket
- Available in flood or bar format
- Ready for connection with power cord and IEC plug
- Advantages of high-power LED technology: extreme light output, long life, low power consumption, defacto maintenance free

### **Technical specifications:**

Power supply:	230 V AC, 50 Hz
Power consumption:	140,00 W
DMX channels:	9; 6
Dimensions:	Length: 88 cm
	Depth: 15 cm
	Height: 16 cm

### Logistic

EAN / GTIN: 4026397388930 Weight: 7,10 kg Length: 0.89 m Width: 0.21 m Heigth: 0.17 m

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.

Weight:	6,55 kg
DMX channels:	max. 27
DMX connection:	3-pin XLR
LED number:	24
LED type:	3 W
Beam angle:	30°
Dimensions (L x W x H):	880 x 150 x 160 mm
Legal specifications	
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting