

## EUROLITE LED PMB-4 COB QCL 30W Bar

LED light effect bar with RGBW color mixing, incl. IR remote control

Art. No.: 51930287

GTIN: 4026397688634



**List price: 355.81 €**

incl. 19% VAT.

### Features:

- 4 powerful LEDs 30 W COB (chip-on-board) 4in1 QCL RGBW (homogenous color mix)
  - Color blend stepless; color change adjustable; color fade adjustable; Dimmer electronic
  - Strobe effect
  - Integrated show programs
  - Direct color selection for 27 preset colors
  - The device is cooled by low-noise cooling fan
  - Control via stand-alone; IR remote control; DMX; Master/slave function; Sound to light via Microphone; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional)
  - Flicker-free
  - With a beam angle of 45°
  - With Mounting bracket
  - LCD display
  - Preprogrammed in Light Captain; EASY SHOW 2; EASY SHOW 1; EASY SHOW 3; Light´J
  - Very quiet working noise
  - Mains input and output for power linking up to 8 units
  - For application areas such as: Wedding/gala/events; Trade fair and shop fitting; Stage; theater; Rental
  - Application possibility: Standing; suspended; on stand
- Package contents**
- 1 x light effect, 1 x power cord, 1 x remote control, 1 x battery, 1 x user manual

### Logistic

EAN / GTIN: 4026397688634  
Weight: 6,35 kg  
Length: 0.54 m  
Width: 0.20 m  
Height: 0.31 m

## Technical specifications:

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	110 W
IP classification:	IP20
Protection class:	Protection class I
Power connection:	Mains input via P-Con (blue), mounting version power supply cord with safety plug (provided)
Power output:	P-Con (gray), mounting version
Fuse:	T 2 A Fuse replaceable
Lamp type:	LED lamp
LED:	4 x 30 W COB (chip-on-board) 4in1 QCL RGBW (homogenous color mix)
Flash rate:	0 - 20 Hz
DMX channels:	3; 4; 5; 6; 8; 16; 20
DMX input:	3-pin XLR (M) mounting version
DMX output:	3-pin XLR (F) mounting version
Cooling:	2 x low-noise cooling fan
Control:	Stand-alone; IR remote control; DMX; Master/slave function; Sound to light via Microphone; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional)
Preprogrammed in:	Light Captain; EASY SHOW 2; EASY SHOW 1; EASY SHOW 3; Light J
Projection:	Flicker-free
Beam angle:	45°
Beam angle (1/2 peak):	45°
Beam angle (1/10 peak):	74°
Housing color:	Black
Attachment system:	Mounting bracket
Display type:	LCD display
Material:	Aluminum casting; metal
Dimensions:	Length: 49,0 cm Depth: 16,3 cm Height: 20,6 cm
Weight:	5,75 kg
Noise classification:	Class 1 (very slight noise, suitable for noise-sensitive environments)
Photobiological safety:	Risk Group 0
Power cord	
Cable construction:	3 x 1,0 mm <sup>2</sup> H05RN-F
Cable length:	Approx. 1,2 m
Mounting bracket	
Diameter mounting holes:	3 x Ø11mm; 1 x Ø10mm; 2 x Ø8mm; 2 x Ø6mm
Material:	Metal, 3 mm

Remote control

---

Battery: 1 x Button cell 3.0 V CR2025 lithium manganese built-in

---

Legal specifications

---

Special product: Not designed for household room illumination

---

Intended use: Show effect lighting

---