eurolite®

EUROLITE LED BAR-252 UV 10mm 15° RC

UV LED bar with infrared remote control



The article is no longer in our assortment.

Features:

- Wide range of UV effects possible
- Perfect for decorative and illumination purposes (i.e. in stairways, cinemas, theaters, corridors or hallways, showrooms, etc.)
- Control via control panel with LED screen, IR remote or any regular DMX512 controller (occupies 2 channels)
- Comfortable addressing and setting via control panel with LED screen and three operating buttons
- Functions: dimming, sound-control, strobe effect, Master/Slave
- Standing or hanging installation possible
- Locking possibility at the mounting brackets
- Extremely compact housing in an appealing design
- Equipped with 252 x 10 mm UV LED
- Ready for connection via power cord with safety power plug
- Control via IR remote control; stand-alone; DMX
- Preprogrammed in Light'J
- With a beam angle of 15°
- Package contents
- 1 x remote control

EAN / GTIN: 4026397435504

Logistic

Weight: 2,60 kg Length: 1.09 m Width: 0.12 m Heigth: 0.13 m

Technical specifications:

Power supply:	230 V AC, 50 Hz
Power consumption:	25 W
IP classification:	IP20

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.

	LED lamp
Control:	IR remote control; stand-alone; DMX
Preprogrammed in:	Light´J
Beam angle:	15°
Beam angle (1/2 peak):	15°
Housing color:	Black
Material:	Metal
Dimensions:	Length: 108 cm
	Depth: 6,5 cm
	Height: 9 cm
Weight:	2,20 kg
Remote control	
Battery:	1 x button cell 3.0 V CR2025 lithium manganese built-in
DMX channels:	2
DMX connection:	3-pin XLR
LED type:	10 mm UV
LED number:	252
Legal specifications	
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting