EUROLITE LED ML-56 COB UV 80W Floor sil

UV LED spot in multi lens design with powerful 80 W COB LED

Art. No.: 51930321

GTIN: 4026397531633

The article is no longer in our assortment.

Features:

- Wide range of UV effects possible
- Functions: dimmer, strobe effect, Master/Slave operation, different dimmer curves/dimmer speed (step response)
- DMX-controlled operation or stand-alone operation with Master/Slave function
- 1 or 3 DMX channels selectable
- Strobe effect with adjustable speed
- Beam angle approximately 35°
- Comfortable addressing and setting via Control Board with LED display and four operating buttons
- Ideal as floor spot via additional bracket
- Locking possibility at the brackets
- Ideal for theatres, large stages as pre-stage spot and mobile use
- Optional color filter frame and barndoors available
- Ready for connection with power cord and safety plug
- Switch-mode power supply for operation between 100 and 240 Volts
- DMX512 control possible via any commercial DMX controller
- Available in silver or in black
- 1 powerful LED 80 W
- Control via stand-alone; DMX
- Preprogrammed in Light´J; LED PC-Control 512
- Flicker-free

Logistic

EAN / GTIN: 4026397531633

Weight: 3,95 kg

Length: 0.29 m

Width: 0.29 m

Heigth: 0.38 m

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn
All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.

Technical specifications:

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	80 W
IP classification:	IP20
Lamp type:	LED lamp
LED:	1 x 80 W
Control:	Stand-alone; DMX
Preprogrammed in:	Light´J; LED PC-Control 512
Projection:	Flicker-free
Beam angle (1/2 peak):	35°
Housing color:	Silver
Material:	Metal
Dimensions:	Width: 29 cm Depth: 25,5 cm Height: 32 cm
Weight:	3,35 kg
DMX channels:	1/3
DMX connection:	3-pin XLR
Flash-rate:	17 Hz
LED number:	1
LED type:	80 W COB, UV
Beam angle:	35°
Dimensions (L x W x H):	255 x 290 x 320 mm
Legal specifications	
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn
All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.