

The article is no longer in our assortment.

Features:

- 8 powerful LEDs 8 W high-power 4in1 QCL RGBW
 LEDs controlled separately
 - 144 powerful LEDs 0,2 W SMD 5050 3in1 TCL RGB (homogenous color mix)
4 segments controlled separately
 - Positioning within 180° TILT
 - Dimmer electronic; color change
 - Multi beam effect
 - 18 integrated show programs
 - Direct color selection for 8 preset colors
 - The device is cooled by passive convection cooling
 - Control via stand-alone; sound to light; IR remote control; DMX; QuickDMX via USB (optional)
 - Flicker-free
 - DMX fail mode (blackout; hold; full on; static; auto)
 - With a beam angle of 1°
 - With omega bracket
 - 4 digit 7-segment LED display
 - 4 rubber feet
 - Mains input and output for power linking up to 8 units
- Package contents**
- 1 x light effect, 1 x user manual, 1 x power cord, 1 x mounting bracket

Logistic

EAN / GTIN: 4026397739558

Technical specifications:

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	120 W

IP classification:	IP20
Protection class:	Protection class I
Power connection:	Mains input via P-Con (blue), mounting version power supply cord with safety plug
Cable construction:	3 x 1,0 mm ² H05VV-F
Cable length:	1,1 m
Power output:	P-Con (gray), mounting version
Fuse:	5 x 20 mm, T 3 A fuse replaceable
Battery:	1 x button cell 3.0 V CR2025 lithium manganese built-in
Lamp type:	LED lamp
LED type:	8 x 8 W high-power 4in1 QCL RGBW 144 x 0,2 W SMD 5050 3in1 TCL RGB (homogenous color mix)
Max. TILT movement:	180° positioning
Flash rate:	1 - 20 Hz
DMX channels:	14; 19; 27; 58
DMX input:	3-pin XLR (M) mounting version
DMX output:	3-pin XLR (F) mounting version
Cooling:	Passive convection cooling
Control:	Stand-alone; sound to light; IR remote control; DMX; QuickDMX via USB (optional)
Projection:	Flicker-free
DMX fail mode:	Blackout; hold; full on; static; auto
Beam angle:	1°
Beam angle (1/2 peak):	Multi beam effect 1°
Beam angle (1/10 peak):	Multi beam effect 1°
Housing color:	Black
Attachment system:	Omega bracket Omega bracket
Display type:	4 digit 7-segment LED display
USB port:	Type A
Transport aid:	4 x rubber feet
Material:	Metal
Dimensions:	Length: 100,0 cm Width: 11,0 cm Height: 18,5 cm
Weight:	8,0 kg
Legal specifications	
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting