

EUROLITE LED BAR-8 ABL SWING QCL bar

Tiltable LED light effect bar with 8 beams and ambient strip

Art. No.: 51930384

GTIN: 4026397739558



Features:

- 8 LEDs 8 W high-power 4in1 RGBW
 LEDs controlled separately
- 144 LEDs 0.2 W SMD 5050 3in1 RGB (homogenous color mix)
4 segments controlled separately
- Positioning within 180° TILT
- Dimmer electronic; color change; color blend adjustable; color fade; color selection
- Multi beam effect; strobe effect
- 8 integrated show programs
- Direct color selection for 18 preset colors
- The device is cooled by passive convection cooling
- Control via stand-alone; sound to light via microphone; IR remote control; DMX; master/slave function; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional)
- Flicker-free
- With a beam angle of 1° multi beam effect
- 4 digit 7-segment LED display
- 4 x rubber feet
- Mains input and output for power linking up to 8 units
- For application areas such as: Clubs/dancing school; party room; mobile djs / entertainer; restaurants, bars and hotels; stage; advertisement/Shop window
- Application possibility: Standing; suspended
- Can be operated in 14; 19; 27; 58 CH mode
- With omega bracket

Logistic

EAN / GTIN: 4026397739558

Weight: 9,30 kg

Length: 1.05 m

Width: 0.16 m

Height: 0.27 m

Technical specifications:

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	120 W
Protection class:	Protection class I
Power connection:	Mains input via P-Con (blue), mounting version power supply cord with safety plug
Cable construction:	3 x 1.0 mm² H05VV-F
Power output:	P-Con (grey), mounting version
Fuse:	5 x 20 mm, T 3 A fuse replaceable
Lamp type:	LED lamp
LED type:	8 x 8 W high-power 4in1 RGBW 144 x 0.2 W SMD 5050 3in1 RGB (homogenous color mix)
Max. TILT movement:	180° positioning
Flash rate:	1 - 20 Hz
DMX channels:	14; 19; 27; 58
DMX input:	3-pin XLR (M) mounting version
DMX output:	3-pin XLR (F) mounting version
Cooling:	Passive convection cooling
Control:	Stand-alone; sound to light via microphone; IR remote control; DMX; master/slave function; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional)
Fixtures available for:	Light Captain; GDTF (GrandMA3)
Projection:	Flicker-free
DMX fail mode:	Blackout; hold; full on; static; auto
Beam angle:	1° multi beam effect
Beam angle (1/2 peak):	Multi beam effect 1°
Beam angle (1/10 peak):	Multi beam effect 1°
Illuminance in Lux (lx):	Red (R) 1m: 4611 lx, 3m: 1616 lx, 6m: 521 lx Green (G) 1m: 9615 lx, 3m: 1319 lx, 6m: 443 lx Blue (B) 1m: 1977 lx, 3m: 191 lx, 6m: 62 lx Cold white (CW) 1m: 10522 lx, 3m: 2400 lx, 6m: 698 lx
Housing color:	Black
Attachment system:	Omega bracket
Display type:	4 digit 7-segment LED display
USB port:	Type A
Transport aid:	4 x rubber feet
Material:	Metal
Dimensions:	Length: 100.0 cm Width: 11.9 cm Height: 20.0 cm
Weight:	8.45 kg
Noise classification:	Class 2 (slight noise)

Battery:

1 x button cell 3.0 V CR2025 lithium manganese
built-in

Scope of delivery:

1 x light effect
1 x user manual
1 x power cord
1 x remote control
1 x battery
1 x omega bracket