

## EUROLITE LED BAR-12 QCL RGB+WW Bar

LED light effect bar (1 m) with RGB+WW color mixing

Art. No.: 51930388

GTIN: 4026397716146



### Features:

- 12 LEDs 7 W high-power 4in1 QCL RGB/WW (homogenous color mix)
  - Color blend stepless; color change adjustable; color fade adjustable; Dimmer electronic
  - Strobe effect
  - 3 integrated show programs
  - Direct color selection for 20 preset colors
  - The device is cooled by passive convection cooling
  - Control via stand-alone; DMX; sound to light via microphone; master/slave function; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional)
  - Fixtures available for EASY SHOW 1; Light´J; EASY SHOW 2; EASY SHOW 3; Colorchief
  - Flicker-free
  - With a beam angle of 20°
  - Variable color temperature 2700 K - 8000 K
  - With mounting bracket
  - 4 digit 7-segment LED display
  - Mains input and output for power linking up to 8 units
  - For application areas such as: Clubs/dancing school; decoration; mobile djs / entertainer; party room; restaurants, bars and hotels; advertisement/Shop window
  - Silent operation
  - Application possibility: Suspended
- knurled screw**
- M6 thread

### Logistic

EAN / GTIN: 4026397716146

Weight: 3,12 kg

Length: 1.03 m

Width: 0.11 m

Heigth: 0.14 m

## Technical specifications:

|                          |   |
|--------------------------|---|
| Power supply:            | 100-240 V AC, 50/60 Hz  |
| Power consumption:       | 25 W  |
| IP classification:       | IP20  |
| Protection class:        | Protection class I  |
| Power connection:        | Mains input via IEC connector (M) mounting version power supply cord with safety plug (provided)  |
| Power output:            | 1 x IEC connector (F) mounting version  |
| Fuse:                    | T 1 A fuse replaceable  |
| Lamp type:               | LED lamp  |
| LED type:                | 12 x 7 W high-power 4in1 QCL RGB/WW (homogenous color mix)  |
| Flash rate:              | 0 - 20 Hz   |
| DMX channels:            | 2; 4; 5; 6; 9   |
| DMX input:               | 3-pin XLR (M) mounting version  |
| DMX output:              | 3-pin XLR (F) mounting version  |
| Cooling:                 | Passive convection cooling  |
| Control:                 | Stand-alone; DMX; sound to light via microphone; master/slave function; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional) |
| Fixtures available for:  | EASY SHOW 1; Light'J; EASY SHOW 2; EASY SHOW 3; Colorchief  |
| Projection:              | Flicker-free  |
| Beam angle:              | 20°   |
| Beam angle (1/2 peak):   | 20°   |
| Beam angle (1/10 peak):  | 33°   |
| Color temperature:       | 2700K - 8000K adjustable  |
| Housing color:           | Black   |
| Attachment system:       | 2x mounting bracket   |
| Display type:            | 4 digit 7-segment LED display   |
| Dimensions:              | Length: 106.00 cm<br>Depth: 8.85 cm<br>Height: 10.90 cm   |
| Weight:                  | 2.68 kg   |
| Noise classification:    | Class 0 (no noise at all)   |
| Cable construction:      | 3 x 0.75 mm <sup>2</sup> H05VV-F  |
| Cable length:            | Approx. 1.2 m   |
| Diameter mounting holes: | 1 x Ø20mm; 1 x Ø11mm; 1 x Ø8mm; 2 x Ø7mm  |
| Material:                | Metal, 2 mm   |
| Color:                   | Black, matte  |
| Diameter mounting holes: | 1 x Ø9mm  |
| Material:                | Plastic, 3 mm   |

|                  |  |
|------------------|--|
| Color:           | Black  |
| Dimensions:      | Diameter: Ø 2 cm                             |
| Thread:          | M6 thread x 18 mm                            |
| Special product: | Not designed for household room illumination |
| Intended use:    | Show effect lighting                         |

### **Scope of delivery:**

---

- 1 x bar
- 1 x user manual
- 1 x power cord
- 2 x mounting bracket
- 2 x washer
- 2 x knurled screw