

## EUROLITE LED BAR-6 QCL RGBA Bar

LED bar (59cm) with 6 x 4 watt 4in1 QCL RGBA LED

Art. No.: 51930397

GTIN: 4026397603538



**List price: 112.93 €**

incl. 19% VAT.

### Features:

- 6 powerful LEDs 4 W high-power 4in1 QCL RGBA (homogenous color mix)
- Color change adjustable; Dimmer electronic; color blend stepless
- Strobe effect
- The device is cooled by passive convection cooling
- Control via stand-alone; DMX; sound to light via microphone; QuickDMX via USB (optional); W-DMX by wireless solution (optional); CRMX by LumenRadio (optional)
- Flicker-free
- With a beam angle of 17°
- With mounting bracket
- 4 digit 7-segment LED display
- Preprogrammed in LED PC-Control 512; Light´J; Light Captain; Colorchief
- Silent operation
- Mains input and output for power linking up to 8 units
- For application areas such as: Clubs/dancing school; party room; restaurants, bars and hotels; small rental
- Application possibility: Suspended; wall mounting

#### Package contents

- 1 x light effect, 2 x mounting bracket, 1 x power cord, 2 x knurled screw, 2 x washer, 1 x user manual

### Logistic

EAN / GTIN: 4026397603538

Weight: 1,95 kg

Length: 0.56 m

Width: 0.12 m

Height: 0.12 m

### Technical specifications:

Power supply: 100-240 V AC, 50/60 Hz

Power consumption: 15 W

|                          |  |
|--------------------------|--|
| IP classification:       | IP20   |
| Power connection:        | Mains input via IEC connector (M) mounting version power supply cord with safety plug (provided)   |
| Power output:            | 1 x IEC connector (F) mounting version   |
| Lamp type:               | LED lamp   |
| LED type:                | 6 x 4 W high-power 4in1 QCL RGBA (homogenous color mix)  |
| Flash rate:              | 0 - 20 Hz  |
| DMX channels:            | 2; 4; 5; 6; 9  |
| DMX input:               | 1 x 3-pin XLR (M) mounting version   |
| DMX output:              | 1 x 3-pin XLR (F) mounting version   |
| Cooling:                 | Passive convection cooling   |
| Control:                 | Stand-alone; DMX; sound to light via microphone; QuickDMX via USB (optional); W-DMX by wireless solution (optional); CRMX by LumenRadio (optional) |
| Preprogrammed in:        | LED PC-Control 512; Light´J; Light Captain; Colorchief   |
| Projection:              | Flicker-free   |
| Beam angle:              | 17°  |
| Beam angle (1/2 peak):   | 17°  |
| Housing color:           | Black matte  |
| Attachment system:       | Mounting bracket   |
| Display type:            | 4 digit 7-segment LED display  |
| Material:                | Aluminum; metal  |
| Dimensions:              | Length: 59 cm<br>Depth: 6,5 cm<br>Height: 10 cm  |
| Weight:                  | 1,75 kg  |
| Noise classification:    | Class 0 (no noise at all)  |
| Photobiological safety:  | Risk Group 0   |
| Mounting bracket         |  |
| Diameter mounting holes: | 1 x Ø20mm; 1 x Ø8mm; 2 x Ø7mm  |
| Material:                | Metal, 2 mm  |
| Power cord               |  |
| Cable construction:      | 3 x 0,75 mm² H05VV-F   |
| Cable length:            | Approx. 1,2 m  |
| Legal specifications     |  |
| Special product:         | Not designed for household room illumination   |
| Intended use:            | Show effect lighting   |