

EUROLITE LED BAR-12 QCL RGBW Bar

LED bar (110cm) with 12 x 4 watt 4in1 QCL RGBW LED

Art. No.: 51930398

GTIN: 4026397603378



Features:

- 12 LEDs 4 W high-power 4in1 QCL RGBW (homogenous color mix)
- Color change adjustable; Dimmer electronic; color blend stepless
- Strobe effect
- The device is cooled by passive convection cooling
- Control via stand-alone; DMX; sound to light via microphone; QuickDMX via USB (optional); W-DMX by wireless solution (optional); CRMX by LumenRadio (optional)
- Fixtures available for LED PC-Control 512; EASY SHOW 1; LED EASY OPERATOR 4x4; LED EASY OPERATOR 4x6; LED EASY OPERATOR DELUXE; Light Captain; Light´J; Colorchief
- Flicker-free
- With a beam angle of 17°
- With mounting bracket
- 4 digit 7-segment LED display
- Mains input and output for power linking up to 8 units
- For application areas such as: Clubs/dancing school; decoration; mobile djs / entertainer; party room; restaurants, bars and hotels; advertisement/Shop window
- Silent operation
- Application possibility: Suspended; wall mounting

Logistic

EAN / GTIN: 4026397603378

Weight: 3,30 kg

Length: 1.06 m

Width: 0.14 m

Height: 0.12 m

Technical specifications:

Power supply: 100-240 V AC, 50/60 Hz

Power consumption: 24 W

IP classification: IP20

Power connection:	Mains input via IEC connector (M) mounting version power supply cord with safety plug (provided)
Power output:	1 x IEC connector (F) mounting version
Fuse:	5 x 20 mm, T 0.5 A fuse replaceable
Lamp type:	LED lamp
LED type:	12 x 4 W high-power 4in1 QCL RGBW (homogenous color mix)
Flash rate:	0.5 - 24 Hz
DMX channels:	2; 4; 5; 6; 9
DMX input:	3-pin XLR (M) mounting version
DMX output:	3-pin XLR (F) mounting version
Cooling:	Passive convection cooling
Control:	Stand-alone; DMX; sound to light via microphone; QuickDMX via USB (optional); W-DMX by wireless solution (optional); CRMX by LumenRadio (optional)
Fixtures available for:	LED PC-Control 512; EASY SHOW 1; LED EASY OPERATOR 4x4; LED EASY OPERATOR 4x6; LED EASY OPERATOR DELUXE; Light Captain; Light J; Colorchief
Projection:	Flicker-free
Beam angle:	17°
Beam angle (1/2 peak):	17°
Beam angle (1/10 peak):	33°
Housing color:	Black
Attachment system:	Mounting bracket
Display type:	4 digit 7-segment LED display
Dimensions:	Length: 110 cm Depth: 6.5 cm Height: 10 cm
Weight:	2.85 kg
Noise classification:	Class 0 (no noise at all)
Photobiological safety:	Risk Group 0
Cable construction:	3 x 0.75 mm ² H05RN-F
Diameter mounting holes:	1 x Ø20mm; 1 x Ø11mm; 1 x Ø8mm; 2 x Ø6mm
Material:	Metal
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting

Scope of delivery:

1 x light effect
1 x power cord
2 x mounting bracket
2 x knurled screw
2 x washer
1 x user manual