

## EUROLITE LED BAR-6 QCL RGBW Bar

LED bar (60 cm) with 6 x 4 W 4in1 LED (RGBW)

Art. No.: 51930399

GTIN: 4026397602890



**List price: 112.93 €**

incl. 19% VAT.

### Features:

- 6 powerful LEDs 4 W high-power 4in1 QCL RGBW (homogenous color mix)
  - Color change adjustable; Dimmer electronic; color blend stepless
  - Strobe effect
  - The device is cooled by passive convection cooling
  - Control via stand-alone; DMX; Sound to light via Microphone; QuickDMX via USB (optional); W-DMX by wireless solution (optional); CRMX by LumenRadio (optional)
  - Flicker-free
  - With a beam angle of 17°
  - With Mounting bracket
  - 4 digit 7-segment LED display
  - Preprogrammed in LED PC-Control 512; EASY SHOW 1; LED EASY OPERATOR 4x4; LED EASY OPERATOR 4x6; LED EASY OPERATOR DELUXE; Light Captain; EASY SHOW 2; EASY SHOW 3; Light'J
  - Silent operation
  - Mains input and output for power linking up to 8 units
  - For application areas such as: Clubs/dancing school; Party room; restaurants, bars and hotels; small rental
  - Application possibility: Suspended; Wall mounting
- Package contents**
- 1 x light effect, 2 x mounting bracket, 1 x power cord, 2 x screw, 2 x washer, 1 x user manual

### Logistic

EAN / GTIN: 4026397602890

Weight: 1,93 kg

Length: 0.60 m

Width: 0.14 m

Height: 0.12 m

### Technical specifications:

Power supply: 100-240 V AC, 50/60 Hz

Power consumption:	15 W
IP classification:	IP20
Power connection:	Mains input via IEC connector (M) mounting version power supply cord with safety plug (provided)
Power output:	1 x IEC connector (F) mounting version
Lamp type:	LED lamp
LED:	6 x 4 W high-power 4in1 QCL RGBW (homogenous color mix)
Flash rate:	0 - 20 Hz
DMX channels:	2; 4; 5; 6; 9
DMX input:	1 x 3-pin XLR (M) mounting version
DMX output:	1 x 3-pin XLR (F) mounting version
Cooling:	Passive convection cooling
Control:	Stand-alone; DMX; Sound to light via Microphone; QuickDMX via USB (optional); W-DMX by wireless solution (optional); CRMX by LumenRadio (optional)
Preprogrammed in:	LED PC-Control 512; EASY SHOW 1; LED EASY OPERATOR 4x4; LED EASY OPERATOR 4x6; LED EASY OPERATOR DELUXE; Light Captain; EASY SHOW 2; EASY SHOW 3; Light'J
Beam angle:	17°
Beam angle (1/2 peak):	17°
Beam angle (1/10 peak):	33°
Housing color:	Black
Attachment system:	Mounting bracket
Display type:	4 digit 7-segment LED display
Material:	Aluminum casting; metal; plastic
Dimensions:	Length: 58,5 cm Depth: 6,5 cm Height: 10 cm
Weight:	1,66 kg
Noise classification:	Class 0 (no noise at all)
Photobiological safety:	Risk Group 0
Power cord	
Cable construction:	3 x 0,75 mm² H05VV-F
Cable length:	Approx. 1,1 m
Mounting bracket	
Diameter mounting holes:	1 x Ø20mm; 1 x Ø11mm; 1 x Ø8mm; 2 x Ø7mm
Material:	Metal, 2 mm
Legal specifications	
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting