

## EUROLITE LED PIX-12 HCL Bar

LED bar (100cm) with 12 x 10 watt 6in1 HCL RGBWA/UV LED

Art. No.: 51930406

GTIN: 4026397602654

**The article is no longer in our assortment.**

### Description:

Light bar (100 cm) with 12 x 10 W 6in1 LED (RGBAW+UV), pixel control

The EUROLITE LED PIX-12 HCL bar features 12 powerful 10 W LEDs (6in1) in red, green, blue, amber, white and UV with a beam angle of 20°. It is suitable for professional applications, for example on show stages or in theatres.

The LED bar provides stepless RGBAW+UV color mixing. Each of the 12 LEDs can be controlled individually. In addition to use in stand-alone mode or via music control, the bar can also be controlled via DMX and in master-slave mode as well as with the supplied infrared remote control.

Addressing and settings can be made via the integrated control board with four control buttons and LED display.

The mains connections allow you to operate up to eight devices in a row.

### Logistic

EAN / GTIN: 4026397602654

Weight: 6,20 kg

Length: 1.03 m

Width: 0.19 m

Height: 0.14 m

### Features:

- 12 powerful LEDs 10 W high-power 6in1 HCL RGBWA/UV (homogenous color mix) LEDs controlled separately
- Color blend stepless; color change adjustable; Dimmer electronic
- Strobe effect; UV effect
- The device is cooled by cooling fan
- Control via stand-alone; DMX; sound to light via microphone; master/slave function; IR remote control
- Flicker-free
- With a beam angle of 20°
- With mounting bracket
- Preprogrammed in Light´J; LED PC-Control 512; EASY SHOW 1; LED EASY OPERATOR 4x6; LED EASY OPERATOR DELUXE; Light Captain; EASY SHOW 2; EASY SHOW 3

- Mains input and output for power linking up to 8 units

#### Package contents

- 1 x spotlight, 1 x user manual, 1 x power cord, 1 x remote control, 1 x battery

### Technical specifications:

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	60 W
IP classification:	IP20
Power connection:	Mains input via IEC connector (M) mounting version power supply cord with safety plug (provided)
Power output:	IEC connector (F) mounting version
Fuse:	T 2 A fuse replaceable
Lamp type:	LED lamp
LED type:	12 x 10 W high-power 6in1 HCL RGBWA/UV (homogenous color mix)
DMX channels:	4; 6; 16; 36; 74
DMX input:	3-pin XLR (M) mounting version
DMX output:	3-pin XLR (F) mounting version
Cooling:	Cooling fan
Control:	Stand-alone; DMX; sound to light via microphone; master/slave function; IR remote control
Preprogrammed in:	Light J; LED PC-Control 512; EASY SHOW 1; LED EASY OPERATOR 4x6; LED EASY OPERATOR DELUXE; Light Captain; EASY SHOW 2; EASY SHOW 3
Projection:	Flicker-free
Beam angle:	20°
Beam angle (1/2 peak):	20°
Beam angle (1/10 peak):	41°
Housing color:	Black
Attachment system:	Mounting bracket
Dimensions:	Length: 100 cm Depth: 11,5 cm Height: 16,5 cm
Weight:	5,20 kg
Photobiological safety:	Risk Group 0
Remote control	
Battery:	1 x button cell 3.0 V CR2025 lithium manganese built-in
Legal specifications	
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting