eurolite®

EUROLITE LED BAR-252 RGB 10mm 20° black

LED bar with 252 LEDs in red, green and blue, 110 cm length and 20°

Art. No.: 51930420 GTIN: 4026397397697







The article is no longer in our assortment.

Description:

Although the dimensions of this LED bar are quite small, the 252 LEDs have lots of power. The color-fading and strobe effects are the most impressive evidences to prove that, especially when they are positioned directly towards the audience. Via a built-in microphone, the LEDs are sound-controled and thus can adapt themselves to the music. The LED bar is a helpful support for bands, on stages and for solo entertainers.

Features:

- DMX512 control via regular DMX controller
- Sound-control via built-in microphone
- Stand-alone mode functions adjustable via DIP switches
- Color change speed and strobe effect adjustable via DIP switches
- Multi-color color changes
- Master/Slave function
- Ideal for bands, stages or solo entertainers
- Perfect in public places, main halls, lounges
- Illuminants: 252 10 mm LEDs (48 x red, 108 x green and 96 x blue)
- Available in 2 LED beam angles: 20° or 40°
- Advantages of LED technology: long life of the LEDs, low power consumption, minimal heat emission, defacto maintenance free with brilliant light radiation
- 252 powerful LEDs 10 mm R/G/B
- Strobe effect
- The device is cooled by passive convection cooling
- Control via stand-alone; DMX; sound to light via microphone
- Preprogrammed in LED PC-Control 512
- With a beam angle of 20°

Logistic

EAN / GTIN: 4026397397697 Weight: 2,60 kg Length: 1.09 m Width: 0.12 m Heigth: 0.13 m

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.

Technical specifications:

Power supply:	230 V AC, 50 Hz
Power consumption:	50,00 W
IP classification:	IP20
Power connection:	Fixed power supply cord with safety plug
Lamp type:	LED lamp
LED type:	252 x 10 mm R/G/B
DMX channels:	12
DMX input:	1 x 3-pin XLR (M) mounting version
DMX output:	1 x 3-pin XLR (F) mounting version
Cooling:	Passive convection cooling
Control:	Stand-alone; DMX; sound to light via microphone
Preprogrammed in:	LED PC-Control 512
Beam angle:	20°
Beam angle (1/2 peak):	20°
Housing color:	Black
Dimensions:	Length: 107 cm
	Depth: 6,5 cm
	Height: 9 cm
Weight:	2,20 kg
Legal specifications	
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting