# eurolite®

### EUROLITE LED BAR-252 RGB 10mm 40° white

LED bar with 252 LEDs







## The article is no longer in our assortment.

#### Features:

- DMX512 control via regular DMX controller
- Sound-control via built-in microphone
- Stand-alone mode functions adjustable via DIP switches
- Color-change speed and strobe effect adjustable via DIP switches
- Multi-color color-changes
- Master/Slave function
- Ideal for bands, stages or solo entertainers
- Perfect in public places, main halls, lounges
- Illuminants: 252 10 mm LEDs (48 x red, 108 x green and 96 x blue)
- Available in 2 LED beam angles: 20° or 40°
- Advantages of LED technology: long life of the LEDs, low power consumption, minimal heat emission, defacto maintenance free with brilliant light radiation
- 252 powerful LEDs 10 mm R/G/B
- Strobe effect
- Control via stand-alone; DMX; sound to light via microphone
- Preprogrammed in LED PC-Control 512
- With a beam angle of 40°

#### **Technical specifications:**

Power supply:	230 V AC, 50 Hz
Power consumption:	50,00 W
IP classification:	IP20

#### Logistic

EAN / GTIN: 4026397397758 Weight: 2,60 kg Length: 1.09 m Width: 0.13 m Heigth: 0.13 m

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.

Power connection:	Fixed power supply cord with safety plug
Lamp type:	LED lamp
LED type:	252 x 10 mm R/G/B
DMX channels:	12
Control:	Stand-alone; DMX; sound to light via microphone
Preprogrammed in:	LED PC-Control 512
Beam angle:	40°
Beam angle (1/2 peak):	40°
Housing color:	White
Dimensions:	Length: 107 cm
	Depth: 6,5 cm
	Height: 9 cm
Weight:	2,25 kg
DMX connection:	3-pin XLR
Legal specifications	
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting