

EUROLITE LED PIX-40 RGB Bar

LED beam bar with narrow beam SMD LEDs (RGB) and pixel control

Art. No.: 51930436

GTIN: 4026397729740

List price: 236.81 €

incl. 19% VAT.

Features:

- 40 powerful LEDs 3 W SMD 3535 3in1 TCL RGB
 LEDs controlled separately
 - Dimmer electronic; color blend stepless; background color adjustable; running light adjustable; program speed adjustable
 - Beam effect
 - 30 integrated show programs
 - Direct color selection
 - The device is cooled by passive convection cooling
 - Control via stand-alone; sound to light; master/slave function; DMX; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional)
 - Flicker-free
 - With a beam angle of 2°
 - With mounting bracket
 - 4 digit 7-segment LED display
 - Mains input and output for power linking up to 8 units
 - Application possibility: Suspended
 - Preprogrammed in Light Captain; Colorchief
 - For application areas such as: Clubs/dancing school; stage; mobile djs / entertainer; restaurants, bars and hotels; rental
 - Silent operation
- Package contents**
- 1 x light effect, 1 x power cord, 1 x user manual

Logistic

EAN / GTIN: 4026397729740

Weight: 3,85 kg

Length: 1.05 m

Width: 0.20 m

Height: 0.11 m

Technical specifications:

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	65 W
IP classification:	IP20
Protection class:	Protection class I
Power connection:	Mains input via P-Con (blue), mounting version power supply cord with safety plug
Power output:	P-Con (gray), mounting version
Device fuse:	T 5 A fuse fix in power supply
Lamp type:	LED lamp
LED type:	40 x 3 W SMD 3535 3in1 TCL RGB
Flash rate:	0,7 - 22 Hz
DMX channels:	3; 11; 120
DMX input:	3-pin XLR (M) mounting version
DMX output:	3-pin XLR (F) mounting version
Cooling:	Passive convection cooling
Control:	Stand-alone; sound to light; master/slave function; DMX; QuickDMX via USB (optional); W- DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional)
Preprogrammed in:	Light Captain; Colorchief
Projection:	Flicker-free
PWM frequency:	12300 Hz
Beam angle:	2°
Beam angle (1/2 peak):	2°
Beam angle (1/10 peak):	5
Housing color:	Black
Attachment system:	Mounting bracket
Display type:	4 digit 7-segment LED display
Dimensions:	Length: 100,5 cm Depth: 8,0 cm Height: 11,5 cm
Weight:	3,25 kg
Noise classification:	Class 0 (no noise at all)
Legal specifications	
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting