

EUROLITE LED PIX-40 RGB Bar

LED beam bar with narrow beam SMD LEDs (RGB) and pixel control

Art. No.: 51930436

GTIN: 4026397729740



Features:

- 40 LEDs 3 W SMD 3535 3in1 TCL RGB
 LEDs controlled separately
- Dimmer electronic; color blend stepless; color animations with two adjustable colors; program speed adjustable
- Beam effect
- 30 integrated show programs
- Direct color selection
- The device is cooled by passive convection cooling
- Control via stand-alone; sound to light; master/slave function; DMX; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional)
- Fixtures available for Light Captain; Colorchief
- Flicker-free
- With a beam angle of 2°
- With mounting bracket
- 4 digit 7-segment LED display
- Mains input and output for power linking up to 8 units
- For application areas such as: Stage; clubs/dancing school; wedding/gala/events; mobile djs / entertainer; theater
- Silent operation
- Application possibility: Suspended

Logistic

EAN / GTIN: 4026397729740

Weight: 3,85 kg

Length: 1.05 m

Width: 0.20 m

Height: 0.11 m

Technical specifications:

Power supply: 100-240 V AC, 50/60 Hz

Power consumption:	65 W
IP classification:	IP20
Protection class:	Protection class I
Power connection:	Mains input via P-Con (blue), mounting version power supply cord with safety plug
Power output:	P-Con (gray), mounting version
Device fuse:	T 5 A fuse fix in power supply
Lamp type:	LED lamp
LED type:	40 x 3 W SMD 3535 3in1 TCL RGB
Flash rate:	0.7 - 22 Hz
DMX channels:	3; 11; 120
DMX input:	3-pin XLR (M) mounting version
DMX output:	3-pin XLR (F) mounting version
Cooling:	Passive convection cooling
Control:	Stand-alone; sound to light; master/slave function; DMX; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional)
Fixtures available for:	Light Captain; Colorchief
Projection:	Flicker-free
PWM frequency:	12300 Hz
Beam angle:	2°
Beam angle (1/2 peak):	2°
Beam angle (1/10 peak):	5
Housing color:	Black
Attachment system:	Mounting bracket
Display type:	4 digit 7-segment LED display
Dimensions:	Length: 100.5 cm Depth: 8.0 cm Height: 11.5 cm
Weight:	3.25 kg
Noise classification:	Class 0 (no noise at all)
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting

Scope of delivery:

1 x light effect
1 x power cord
1 x user manual