

EUROLITE LED BAR-1250 RGB+UV 4in1

LED bar (110cm) with 12 x 5 watt 4in1 QCL RGB/UV LED

Art. No.: 51930440 GTIN: 4026397572285



The article is no longer in our assortment.

Features:

- Equipped with twelve QCL LEDs in the colors red, green, blue and UV
- 1, 3, 4, 6, 7 or 12 DMX channels selectable
- DMX-controlled operation or stand-alone operation with Master/Slave function
- Addressing and setting via Control Board with LED display and four operating buttons
- Additional controlling possibility via the EUROLITE IR-8 remote control, included in delivery
- Functions: Static colors, RGBUV color blend, internal programs, dimmer and strobe settings via DMX, Master/Slave
- Every LED group (each with 4 LEDs) can be controlled individually in 12CH mode
- Sound-control via built-in microphone
- Hanging as well as standing installation possible
- Locking possibility at the brackets
- Switch-mode power supply for operation between 100 and 240 volts
- DMX control via every standard DMX controller
- Feed-through output allows to power up to 8 devices
- Ready for connection via enclosed IEC power cord with safety-plug
- 12 powerful LEDs 5 W high-power 4in1 QCL RGB/UV (homogenous color mix)
- Strobe effect; UV effect
- Control via stand-alone; DMX; IR remote control; sound to light via microphone
- Preprogrammed in Light'J; LED PC-Control 512
- Flicker-free
- With a beam angle of 20°

Package contents

1 x remote control

Logistic

EAN / GTIN: 4026397572285

Weight: 3,57 kg Length: 1.09 m Width: 0.12 m Heigth: 0.13 m

Technical specifications:

| - Common openinguione. | |
|-------------------------|--|
| Power supply: | 100-240 V AC, 50/60 Hz |
| Power consumption: | 55 W |
| IP classification: | IP20 |
| Power connection: | Mains input via IEC connector (M) mounting version power supply cord with safety plug (provided) |
| Power output: | 1 x IEC connector (F) mounting version |
| Lamp type: | LED lamp |
| LED type: | 12 x 5 W high-power 4in1 QCL RGB/UV (homogenous color mix) |
| DMX channels: | 1; 3; 4; 6; 7; 12 |
| DMX input: | 1 x 3-pin XLR (M) mounting version |
| DMX output: | 1 x 3-pin XLR (F) mounting version |
| Control: | Stand-alone; DMX; IR remote control; sound to light via microphone |
| Preprogrammed in: | Light'J; LED PC-Control 512 |
| Projection: | Flicker-free |
| Beam angle: | 20° |
| Beam angle (1/2 peak): | 20° |
| Beam angle (1/10 peak): | 38° |
| Housing color: | Black |
| Dimensions: | Length: 110 cm Depth: 8 cm Height: 6,2 cm |
| Weight: | 3,19 kg |
| Remote control | |
| Battery: | 1 x button cell 3.0 V CR2025 lithium manganese built-in |
| Legal specifications | |
| Special product: | Not designed for household room illumination |
| Intended use: | Show effect lighting |
| | |