eurolite®

EUROLITE LED BAR-252 RGBA 10mm 20° white

Versatile LED-RGBA color changer



The article is no longer in our assortment.

Features:

- Operable in stand-alone mode or via DMX
- DMX512 control possible via any commercial DMX controller (occupies max.19 channels)
- 4, 6 or 19 DMX channels selectable for numerous applications
- Sound-control via built-in microphone
- Comfortable addressing and setting via control panel with LCD display and four operating buttons
- Functions: Static colors, RGBA color blend, internal programs, dimmer and strobe settings via DMX, Master/Slave
- Equipped with 252 x 10 mm LED
- Locking possibility at the mounting bracket
- Ready for connection with power cord and safety plug
- Available in 2 LED beam angles: 20° or 40°
- Available in black or white housing
- Advantages of high-power LED technology: extreme light output, long life, low power consumption, defacto maintenance free with brilliant light radiation
- Control via DMX

IP classification:

- Preprogrammed in Light'J

Technical specifications: Power supply: 230 V AC, 50 Hz Power consumption: 24,00 W

IP20

Logistic

EAN / GTIN: 4026397429008 Weight: 3,00 kg Length: 1.09 m Width: 0.14 m Heigth: 0.14 m

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.

Control:	DMX
Preprogrammed in:	Light´J
Dimensions:	Length: 1,08 m Depth: 6,5 cm Height: 9 cm
Weight:	2,65 kg
DMX channels:	max. 19: 4 / 6 / 19
DMX connection:	3-pin XLR
Sound-control:	via built-in microphone
LED type:	10 mm
LED number:	252
Beam angle:	20°
Dimensions (L x W x H):	1075 x 65 x 90 mm
Legal specifications	
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting