# EUROLITE LED Space Ball 35 MK3 + HST-200

**Art. No.: 51930453**

GTIN: 4026397700725

## The article is no longer in our assortment.

### Features:

- For application areas such as: Clubs/dancing school; Wedding/gala/events; restaurants, bars and hotels
- Application possibility: Suspended
- <p>EUROLITE LED Space Ball 35 MK3
- <p class="featureSatz">Modern LED ambient light with DMX control
- Particularly impressive when used in larger quantities
- 6 powerful LEDs 7 W high-power 3in1 TCL RGB (homogenous color mix)
- The device is cooled by passive convection cooling
- Control via system controller
- For application areas such as: Wedding/gala/events; Clubs/dancing school; restaurants, bars and hotels
- Color blend stepless; Dimmer electronic; effect speed adjustable

**Package contents**

- 1 x light effect
- <p>EUROLITE HST-200 Hoist
- <p class="featureSatz">Hoist for LED Space Balls 20, 35 and LED Space Tube 100
- Control via DMX
- Preprogrammed in LED PC-Control 512
- With Omega bracket
- 3 digit 7-segment LED display
- Lifting height: 2 m
- For application areas such as: Clubs/dancing school; Wedding/gala/events; restaurants, bars and hotels
- Application possibility: Suspended

**Package contents**

- 1 x device, 1 x user manual

### Logistic

EAN / GTIN: 4026397700725

Weight: 12,00 kg

Length: 0.82 m

Width: 0.41 m

Heigth: 0.52 m

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn
All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.

## Technical specifications:

| | |
|---|---|
| Weight: | 7,75 kg |
| Noise classification: | Class 2 (slight noise) |

**EUROLITE LED Space Ball 35 MK3**

| | |
|---|---|
| Power supply: | 24 V |
| Power consumption: | 7,2 W |
| IP classification: | IP20 |
| Protection class: | Protection class III |
| Power connection: | Via 4-pin screw plug connector (M) mounting version |
| LED type: | 6 x 7 W high-power 3in1 TCL RGB (homogenous color mix) |
| Cooling: | Passive convection cooling |
| Control: | System controller |
| Housing color: | White |
| Dimensions: | Diameter: Ø 35 cm |
| Weight: | 1,50 kg |

**EUROLITE HST-200 Hoist**

| | |
|---|---|
| Power supply: | 230 V AC, 50 Hz |
| Power consumption: | 50 W |
| Protection class: | Protection class I |
| Power connection: | Fixed power supply cord with safety plug |
| Fuse: | T 1,5 A |
| DMX channels: | 8 |
| DMX input: | 3-pin XLR (M) mounting version |
| DMX output: | 3-pin XLR (F) mounting version |
| Control: | DMX |
| Preprogrammed in: | LED PC-Control 512 |
| Attachment system: | Omega bracket |
| Display type: | 3 digit 7-segment LED display |
| Lifting height: | 2 m |
| Dimensions: | Width: 23,5 cm<br>Depth: 11 cm<br>Height: 21 cm |
| Weight: | 6,25 kg |
| Noise classification: | Class 2 (slight noise) |

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn
All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.