eurolite®

EUROLITE LED Space Tube 100 + HST-500

GTIN: 4026397716214









List price: 1034.11 €

incl. 19% VAT.

Features:

- For application areas such as: Clubs/dancing school; wedding/gala/events; restaurants, bars and hotels
- Application possibility: Suspended
- EUROLITE LED Space Tube 100 for HST Hoist
- Modern LED ambient light with DMX control
- Vertical and horizontal position with two hoists possible
- Particularly impressive when used in larger quantities
- 60 powerful LEDs high-power 3in1 TCL RGB (homogenous color mix)
- Color blend stepless; Dimmer electronic; effect speed adjustable
- The device is cooled by passive convection cooling
- Control via DMX
- For application areas such as: Wedding/gala/events; clubs/dancing school; restaurants, bars and hotels
- Package contents
- 1 x light effect
- EUROLITE HST-500 Hoist
- Hoist for LED Space Balls 20, 35 and LED Space Tube 100
- Control via DMX
- With omega bracket
- 4 digit 7-segment LED display
- Lifting height: 5 m
- Package contents
- 1 x device, 1 x user manual

Logistic

EAN / GTIN: 4026397716214 Weight: 13,00 kg Length: 0.00 m Width: 0.00 m Heigth: 0.00 m

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.

Technical specifications:

Weight:	11,30 kg
Noise classification:	Class 2 (slight noise)

EUROLITE LED Space Tube 100 for HST Hoist

Power supply:	24V DC
IP classification:	IP20
Protection class:	Protection class III
LED type:	60 x high-power 3in1 TCL RGB (homogenous color mix)
Cooling:	Passive convection cooling
Control:	DMX
Housing color:	White
Dimensions:	Length: 100 cm Diameter: Ø 58 cm
Weight:	0,78 kg
Legal specifications	
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting

EUROLITE HST-500 Hoist

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	50 W
Protection class:	Protection class I
Power connection:	Fixed power supply cord with safety plug
DMX channels:	8
DMX input:	3-pin XLR (M) mounting version
DMX output:	3-pin XLR (F) mounting version
Control:	DMX
Attachment system:	Omega bracket
Display type:	4 digit 7-segment LED display
Lifting height:	5 m
Dimensions:	Width: 39,5 cm
	Depth: 15,0 cm
	Height: 43,0 cm
Weight:	9,45 kg