eurolite®

EUROLITE LED DL-79-3-NK-W Ceiling light

LED-downlight

Art. No.: 51935900

GTIN: 4026397220018



The article is no longer in our assortment.

Features:

- Compact downlight for innovative illumination of bars, malls, restaurants or shops
- LED starlights or fancy fair installations can be realized
- 3 white high-power LEDs (1 Watt)
- Fixation via clamps
- Little mounting depth
- Power supply via optional transformer
- Advantages of high-power LED technology: extreme light output, long life, low power consumption, defacto maintenance free
- Installation ring nickle color
- Luminaire without connection terminal. For the connection, instructions of qualified personnel may be necessary.
- Installation only by professional installers or electricians

Technical specifications:

Power consumption:	6,50 W	
Dimensions:	Width: 7,9 cm	
	Depth: 3 cm	
	Height: 7,9 cm	
Power supply:	10.5 V DC	
LED number:	3	
Beam angle:	10-15°	

Logistic

EAN / GTIN: 4026397220018 Weight: 0,25 kg Length: 0.10 m Width: 0.09 m Heigth: 0.06 m

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.

Installation hole:	73 mm
Minimum mounting depth:	35 mm
Dimensions (L x W x H):	79 x 79 x 30 mm
Weight:	0.2 kg