eurolite®

EUROLITE LED DL-42-1-NK-B Ceiling light

Swivable LED-downlight

Art. No.: 51935911 GTIN: 4026397270235





The article is no longer in our assortment.

Features:

- Compact downlight for innovative illumination of bars, malls, restaurants or shops
- LED starlights or fancy fair installations can be realized
- 1 blue high-power LED (1 Watt)
- Fixation via clamps
- Little mounting depth
- Power supply via optional transformer
- Advantages of high-power LED technology: extreme light output, long life, low power consumption, defacto maintenance free
- Installation ring nickle color
- Luminaire without connection terminal. For the connection, instructions of qualified personnel may be necessary.
- Installation only by professional installers or electricians

Technical specifications:

Power consumption:	3,50 W	
IP classification:	IP33	
Dimensions:	Width: 5,3 cm	
	Depth: 3,5 cm	
	Height: 5,3 cm	
Power supply:	3.5 V DC	
Protection grade:	IP33	

Logistic

EAN / GTIN: 4026397270235 Weight: 0,14 kg Length: 0.07 m Width: 0.07 m Heigth: 0.04 m

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.

LED number:	1 x 1 W
Beam angle:	10-15°
Swivel angle:	30°
Installation hole:	43 mm
Minimum mounting depth:	35 mm
Dimensions (L x W x H):	53 x 53 x 35 mm
Weight:	0.11 kg
Legal specifications	
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting