EUROLITE LED Strobe COB PRO 8x20W DMX RGB

Strobe with 8 x 20 W COB LED with RGB color mixing

Art. No.: 52200872

GTIN: 4026397615470

The article is no longer in our assortment.

Description:

This LED strobe is equipped with 8 x 20-watt RGB COB LEDs and combines strobe and blinder effects. It lets you create both dynamic stage shows and the more low-key effects in between with a single fixture.

You can choose from three different operation modes: master-slave, stand-alone and DMX mode (7 DMX channels). The integrated microphone makes for great light effects to the rhythm of the music.
The fixture has 3-pin DMX connectors as well as an IEC input to connect it to the mains.

Features:

- Operable in stand-alone mode or via DMX
- Equipped with eight powerful 20 W RGB COB LEDs
- Addressing and setting via control board with LED display and four operating buttons
- Functions: internal programs, Blinder effect, dimmer, Master/Slave
- Elaborate reflector system
- Compact housing with mounting bracket and fixation screws
- Switch-mode power supply for operation between 100 and 240 Volts
- Ready for connection via included IEC power cord with safety power plug
- 8 powerful LEDs 20 W COB (chip-on-board) 3in1 TCL RGB (homogenous color mix)
- Strobe effect
- Control via DMX; Sound to light via Microphone
- Preprogrammed in Light´J; LED PC-Control 512
- 4 digit 7-segment LED display

Package contents

- 1 x device, 1 x power cord, 1 x user manual

Logistic

EAN / GTIN: 4026397615470
Weight: 2,50 kg
Length: 0.09 m
Width: 0.36 m
Heigth: 0.18 m

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn
All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.

Technical specifications:

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	120 W
IP classification:	IP20
Protection class:	Protection class I
Power connection:	Mains input via IEC connector (M) mounting version power supply cord with safety plug included
Cable length:	1,4 m
Lamp type:	LED lamp
LED:	8 x 20 W COB (chip-on-board) 3in1 TCL RGB (homogenous color mix)
DMX channels:	7
DMX input:	1 x 3-pin XLR (M) mounting version
DMX output:	1 x 3-pin XLR (F) mounting version
Control:	DMX; Sound to light via Microphone
Preprogrammed in:	Light´J; LED PC-Control 512
Display type:	4 digit 7-segment LED display
Dimensions:	Width: 36,5 cm Depth: 9 cm Height: 18,5 cm
Weight:	2,29 kg
Legal specifications	
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn
All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.