

The article is no longer in our assortment.

Features:

- 864 powerful LEDs 0,2 W SMD 5050 3in1 TCL RGB (homogenous color mix)
8 segments controlled separately
 - 288 powerful LEDs 0,5 W SMD 5050 cold white (CW)
3 segments controlled separately
 - Dimmer
 - Strobe effect
 - 7 integrated show programs
 - Direct color selection for 18 preset colors
 - The device is cooled by cooling fan
 - Control via sound to light via microphone; stand-alone; DMX; QuickDMX via USB (optional); W-DMX by wireless solution via USB; CRMX by LumenRadio via USB; IR remote control; master/slave function
 - Flicker-free
 - DMX fail mode (blackout; hold; full on; static; auto)
 - With a beam angle of 120°
 - With double bracket
 - LCD display
 - Mains input and output for power linking up to 8 units
- Package contents**
- 1 x light effect, 1 x user manual, 1 x power cord

Logistic

EAN / GTIN: 4026397744866

Technical specifications:

Power supply: 100-240 V AC, 50/60 Hz

Power consumption: 200 W

IP classification:	IP20
Protection class:	Protection class I
Power connection:	Mains input via P-Con (blue), mounting version power supply cord with safety plug
Cable construction:	3 x 1,0 mm ² H05VV-F
Power output:	P-Con (gray), mounting version
Fuse:	5 x 20 mm, T 3 A fuse replaceable
Lamp type:	LED lamp
LED type:	864 x 0,2 W SMD 5050 3in1 TCL RGB (homogenous color mix) 288 x 0,5 W SMD 5050 cold white (CW)
Flash rate:	0,5 - 20 Hz
DMX channels:	4; 6; 7; 9; 16; 32
DMX input:	3-pin XLR (M) mounting version
DMX output:	3-pin XLR (F) mounting version
Cooling:	4 x cooling fan
Control:	Sound to light via microphone; stand-alone; DMX; QuickDMX via USB (optional); W-DMX by wireless solution via USB; CRMX by LumenRadio via USB; IR remote control; master/slave function
Projection:	Flicker-free
PWM frequency:	7700 Hz
DMX fail mode:	Blackout; hold; full on; static; auto
Beam angle:	120°
Beam angle (1/2 peak):	120°
Beam angle (1/10 peak):	190°
Housing color:	Black
Attachment system:	Double bracket
Display type:	LCD display
USB port:	Type A
Diameter mounting holes:	3 x Ø10mm
Material:	Metal
Dimensions:	Width: 47,0 cm Depth: 11,5 cm Height: 33,0 cm
Weight:	5,95 kg
Remote control	
Battery:	1 x button cell 3.0 V CR2025 lithium manganese built-in