# eurolite®

### EUROLITE LED Mega Strobe 812 Panel

3in1 LED effect light with RGB color mixing and DMX











## List price: 593.81 €

incl. 19% VAT.

#### Features:

- 140 powerful LEDs 3 W SMD 3535 cold white (CW)
- 672 powerful LEDs 0,2 W SMD 5050 3in1 TCL RGB (homogenous color mix)
- Strobe effect; wash effect; Blinder effect
- 37 integrated show programs
- The device is cooled by cooling fan
- Control via stand-alone; DMX; master/slave function
- Flicker-free
- With mounting bracket
- LCD display
- Dimmer curves adjustable; color blend stepless; Dimmer electronic
- Preprogrammed in Light Captain
- For application areas such as: Clubs/dancing school; wedding/gala/events; stage; mobile djs / entertainer; rental
- Very quiet working noise
- Application possibility: Suspended; on stand Package contents
- 1 x light effect, 1 x user manual, 1 x power cord

# Technical specifications: Power supply: 100-240 V AC, 50/60 Hz Power consumption: 400 W IP classification: IP20

#### Logistic

EAN / GTIN: 4026397707595 Weight: 8,20 kg Length: 0.52 m Width: 0.22 m Heigth: 0.34 m

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.

Protection class:	Protection class I
Power connection:	Mains input via P-Con (blue), mounting version (provided)
Power output:	1 x P-Con (gray), mounting version
Fuse:	T 3 A fuse replaceable
LED type:	140 x 3 W SMD 3535 cold white (CW) 672 x 0,2 W SMD 5050 3in1 TCL RGB (homogenous color mix)
Flash rate:	1 - 30 Hz
DMX channels:	6; 17; 20; 21; 298; 310
DMX input:	5-pin XLR (M) mounting version 3-pin XLR (M) mounting version
DMX output:	5-pin XLR (F) mounting version 3-pin XLR (F) mounting version
Cooling:	Cooling fan
Control:	Stand-alone; DMX; master/slave function
Preprogrammed in:	Light Captain
Projection:	Flicker-free
Beam angle (1/2 peak):	120°
Attachment system:	Mounting bracket
Display type:	LCD display
Dimensions:	Width: 50,0 cm Depth: 14,5 cm Height: 27,5 cm
Weight:	7,45 kg
Noise classification:	Class 1 (very slight noise, suitable for noise- sensitive environments)