EUROLITE CH-2 Strobe Control

2-channel strobe controller

Art. No.: 52202212

GTIN: 4026397127584

The article is no longer in our assortment.

Features:

- Speed control
- Auto/Manual switch
- Short flashing by hand
- 6 programs selectable
- Channels individually selectable
- Flashing rate selectable per program
- This controller can control all analogue strobes
- Up to 5 strobes can be connected
- Connection via 6.3 mm jack plug
- Compact housing
- Steplessly adjustable speed control (0.5 - 30 flashes/sec.)

Technical specifications:

Power consumption:	20,00 W
Dimensions:	Width: 16 cm Depth: 12,5 cm Height: 13 cm
Weight:	1,10 kg
Power supply:	230 V AC
Output signal:	0/10 V impulses
Maximum load:	5 Strobes

Logistic

EAN / GTIN: 4026397127584
Weight: 1,40 kg
Length: 0.23 m
Width: 0.17 m
Heigth: 0.20 m

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn
All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.

Dimensions:	160 x 130 x 125 mm

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn
All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.