eurolite®

EUROLITE Strobe Controller

Thoroughly developed strobe control





The article is no longer in our assortment.

Features:

- Rack installation

- Built-in microphone for sound control
- 4 channels
- Flash button
- 6 programs selectable
- Channels individually selectable
- Flashes selectable per program section
- Auto/manual/audio switch
- Speed control
- Can control all analogue strobes
- Up to 5 strobes can be connected
- Connection via 6.3 mm jack plug
- Steplessly adjustable speed control (0.5 30 flashes/sec)
- LED display for flash rate
- Control via analog 0-10 V

Logistic

EAN / GTIN: 4026397127607 Weight: 1,90 kg Length: 0.52 m Width: 0.17 m Heigth: 0.13 m

Technical specifications:

Power supply:	230 V AC, 50 Hz
Power consumption:	20 W
Control:	Analog 0-10 V
Dimensions:	Width: 48 cm
	Depth: 7 cm

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.

1,74 kg	
0/10 V impulses	
5 Strobes	
480 x 70 x 90 mm	
	0/10 V impulses 5 Strobes