

# **EUROLITE AKKU LED Party Tube IR**

Battery operated LED color tube with IR remote control

Art. No.: 52500216 GTIN: 4026397713275



List price: 83.18 €

incl. 19% VAT.

#### Features:

- Extraordinary lighting for an enchanting atmosphere
- The milky PVC housing provides for a lovely appearance as well as for atmospheric illumination
- Incl. 3 easy-to-connect parts as stand for upright mounting and clips for wall or ceiling mounting
- Battery operation up to 8h
- 32 powerful LEDs SMD 5050 3in1 TCL RGB
- Program speed adjustable; Dimmer electronic
- Strobe effect
- 10 integrated show programs
- Direct color selection for 12 preset colors
- Control via on/off switch on device; IR remote control
- With a beam angle of 300°
- Cordless, flexible and versatile
- For application areas such as: Wedding/gala/events; party room; restaurants, bars and hotels; advertisement/Shop window
- Silent operation
- Application possibility: Standing; wall mounting

## Package contents

 1 x device, 1 x user manual, 1 x external mains adapter, 1 x remote control, 2 x mounting bracket, 3 x stand, 1 x battery

## **Technical specifications:**

Power supply:	12,6V DC
IP classification:	IP20

#### Logistic

EAN / GTIN: 4026397713275

Weight: 0,72 kg Length: 1.12 m Width: 0.08 m Heigth: 0.06 m

Power connection:  Mains input via coaxial power connector (M) power supply cord with AC adapter (provided)  Battery pack type:  1 x lithium ion 11,1 V, 2500 mAh, 27,7 Wh  Battery pack:  Battery operation up to 8h Recharging time 4h  Battery:  1 x button cell 3.0 V CR2025 lithium manganese built-in  Lamp type:  LED lamp  LED type:  32 x SMD 5050 3in1 TCL RGB  Flash rate:  0 - 30 Hz  Control:  On/off switch on device; IR remote control  Beam angle:  300°  Beam angle (1/2 peak):  300° multicolor  Housing color:  White; semi-transparent  Dimensions:  Width: 20 cm  Height: 100 cm  Diameter: Ø 5 cm  Weight:  0,56 kg  Noise classification:  Class 0 (no noise at all)	Protection class:	Protection class III
Battery pack:  Battery operation up to 8h Recharging time 4h  Battery:  1 x button cell 3.0 V CR2025 lithium manganese built-in  Lamp type:  LED lamp  LED type:  32 x SMD 5050 3in1 TCL RGB  Flash rate:  0 - 30 Hz  Control:  On/off switch on device; IR remote control  Beam angle:  300°  Beam angle (1/2 peak):  300° multicolor  Housing color:  White; semi-transparent  Dimensions:  Width: 20 cm Height: 100 cm Diameter: Ø 5 cm  Weight:  0,56 kg	Power connection:	
Recharging time 4h  Battery:  1 x button cell 3.0 V CR2025 lithium manganese built-in  Lamp type:  LED lamp  LED type:  32 x SMD 5050 3in1 TCL RGB  Flash rate:  0 - 30 Hz  Control:  On/off switch on device; IR remote control  Beam angle:  300°  Beam angle (1/2 peak):  Housing color:  White; semi-transparent  Dimensions:  Width: 20 cm  Height: 100 cm  Diameter: Ø 5 cm  Weight:  0,56 kg	Battery pack type:	1 x lithium ion 11,1 V, 2500 mAh, 27,7 Wh
built-in  Lamp type:  LED lamp  LED type:  32 x SMD 5050 3in1 TCL RGB  Flash rate:  0 - 30 Hz  Control:  On/off switch on device; IR remote control  Beam angle:  300°  Beam angle (1/2 peak):  Housing color:  White; semi-transparent  Dimensions:  Width: 20 cm  Height: 100 cm  Diameter: Ø 5 cm  Weight:  0,56 kg	Battery pack:	
LED type:  32 x SMD 5050 3in1 TCL RGB  Flash rate:  0 - 30 Hz  Control:  On/off switch on device; IR remote control  Beam angle:  300°  Beam angle (1/2 peak):  Housing color:  White; semi-transparent  Dimensions:  Width: 20 cm  Height: 100 cm  Diameter: Ø 5 cm  Weight:  0,56 kg	Battery:	1 x button cell 3.0 V CR2025 lithium manganese built-in
Flash rate:  O - 30 Hz  Control:  On/off switch on device; IR remote control  Beam angle:  300°  Beam angle (1/2 peak):  Housing color:  White; semi-transparent  Width: 20 cm Height: 100 cm Diameter: Ø 5 cm  Weight:  0,56 kg	Lamp type:	LED lamp
Control:  On/off switch on device; IR remote control  Beam angle:  300°  Beam angle (1/2 peak):  Housing color:  White; semi-transparent  Width: 20 cm Height: 100 cm Diameter: Ø 5 cm  Weight:  0,56 kg	LED type:	32 x SMD 5050 3in1 TCL RGB
Beam angle: 300°  Beam angle (1/2 peak): 300° multicolor  Housing color: White; semi-transparent  Dimensions: Width: 20 cm Height: 100 cm Diameter: Ø 5 cm  Weight: 0,56 kg	Flash rate:	0 - 30 Hz
Beam angle (1/2 peak):  Housing color:  White; semi-transparent  Width: 20 cm  Height: 100 cm  Diameter: Ø 5 cm  Weight:  0,56 kg	Control:	On/off switch on device; IR remote control
Housing color:  White; semi-transparent  Width: 20 cm Height: 100 cm Diameter: Ø 5 cm  Weight:  0,56 kg	Beam angle:	300°
Dimensions:  Width: 20 cm Height: 100 cm Diameter: Ø 5 cm  Weight:  0,56 kg	Beam angle (1/2 peak):	300° multicolor
Height: 100 cm  Diameter: Ø 5 cm  Weight: 0,56 kg	Housing color:	White; semi-transparent
	Dimensions:	Height: 100 cm
Noise classification: Class 0 (no noise at all)	Weight:	0,56 kg
	Noise classification:	Class 0 (no noise at all)