

EUROLITE Safety Bond A 3x600mm up to 5kg, silver

Approved safety bond

Art. No.: 58010310

GTIN:



Description:

EUROLITE Safety bonds

The EUROLITE safety bonds comply with the current regulation of the German professional insurance association as summed up in BGI 810-3:2007-03 Loads above persons. The safety bonds are constructed in accordance with the European standards DIN EN 12385-4:2008-06 and DIN 56927:2009-03.

The safety bonds are tested by the LGA, an independent and accredited testing institute. The breaking load testified by the LGA is documented in the test report according to DIN EN 10204 required by the German professional insurance association.

Clearly, every user can secure loads above persons with these safety bonds in all areas where the BGV C1 is required.

Logistic

Features:

- Rope with thimble and connector
- For further information about this product, please refer to the Data Sheet under "Downloads"
- <p>EUROLITE Steel Rope 600x3mm silver with Thimbles
- <h2 class="featureSatz">Installation rope, safety bond, safety</h2>Round strand rope 6 x 19 with fibre core
- Suitable for installing and securing loads above persons
- Complies with DIN EN 12385-4:2008-06 and DIN 56927:2009-03
- Rope with thimble
- For further information about this product, please refer to the Data Sheet under "Downloads"
- <p>EUROLITE Quick Link Type A-50
- <h2 class="featureSatz">Quick link</h2>Complies with DIN 56927:2009-03

Technical specifications:

Secured weight (BGV C1):	Max. 5 kg
Strength classification:	1770
Temperature range:	-40° C - +100° C
Weight:	0.04 kg

EUROLITE Steel Rope 600x3mm silver with Thimbles

Maximum load WLL (5-fold):	100 kg
Design of the core:	6 x 19 FC
Strength classification:	1960
Standard:	DIN EN 12385-4:2008-06, DIN 56927:2009-03
Nominal tensile strenght of rope:	1770 N/mm ²
Wire surface:	Zinc-plated
Color:	Silver
Temperature range:	-40° C - +100° C
Dimensions:	Length: 60 cm Diameter: Ø 0.30 cm
Weight:	0.03 kg
Length weigth:	0.0311 kg/m

EUROLITE Quick Link Type A-50

Maximum load WLL (10-fold):	50 kg
Standard:	DIN 56927:2009-03,
Shape:	A - small opening
Material:	Steel, zinc-plated
Opening:	0-5 mm
Dimensions:	Length: 2.90 cm Width: 3.50 cm Depth: 1.90 cm Diameter: Ø 0.30 cm
Weight:	0.01 kg

Scope of delivery:
