

## EUROLITE Steel rope 900x6mm black

Simple steel rope

Art. No.: 58010448

GTIN:



**The article is no longer in our assortment.**

### Features:

Simple steel rope

- Suitable for installing light loads
- With two loops
- 6 mm quick link (form A) included
- For further information about this product, please refer to the Data Sheet under "Downloads"

### Logistic

#### EUROLITE Steel rope 900x6mm black without quick link

Simple steel rope

- Suitable for installing light loads
- With two loops
- For further information about this product, please refer to the Data Sheet under "Downloads"

#### EUROLITE Quick link Typ A-200 black

Quick link

- Complies with DIN 56927:2009-03
- Nominal size: 6 mm
- Form A (short)
- Galvanized
- Identification number: 200
- Stamp: DIN 56927 A 200
- Test report according to DIN EN 10204 as download
- Complies with DIN 56927:2009-03

- For further information about this product, please refer to the Data Sheet under "Downloads"

## Technical specifications:

---

Maximum load WLL (5-fold):	360 kg
Weight:	250 g
Maximum load WLL (5-fold):	360 kg
Temperature range:	-40° C to +100° C
Rope length:	0.9 m
Rope diameter:	6 mm
Weight:	0.2 kg

### **EUROLITE Steel rope 900x6mm black without quick link**

Maximum load WLL (5-fold):	360 kg
Temperature range:	-40° C - +100° C
Dimensions:	Length: 90 cm
Maximum load WLL (5-fold):	360 kg
Temperature range:	-40° C to +100° C
Rope length:	0.9 m
Rope diameter:	6 mm

### **EUROLITE Quick link Typ A-200 black**

Maximum load WLL (5-fold):	400 kg
Standard:	DIN 56927:2009-03,
Dimensions:	Width: 5,80 cm Depth: 2,70 cm
Maximum load WLL (5-fold):	400 kg
Maximum load BGV C1 (10-fold):	200 kg
Identification:	DIN 56926-A-200
Temperature range:	-40° C to +100° C
Diameter:	6 mm
Form:	A - small
Spanner opening:	7.5 mm
Dimensions:	58 x 27 mm
Weight:	30 g