# eurolite®

### EUROLITE Steel rope 1400x6mm silver

Simple steel rope

## The article is no longer in our assortment.

#### Features:

Simple steel rope

- Suitable for installing light loads
- With two loops
- 6 mm quick link (form A) included
- For further information about this product, please refer to the Data Sheet under "Downloads"

#### EUROLITE Steel rope 1400x6mm silver without quick link

Simple steel rope

- Suitable for installing light loads
- With two loops
- For further information about this product, please refer to the Data Sheet under "Downloads"

#### EUROLITE Quick Link Type A-200

#### Quick link

- Complies with DIN 56927:2009-03
- For further information about this product, please refer to the Data Sheet under "Downloads"

#### **Technical specifications:**

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.



Art. No.: 5801044A

GTIN:

Logistic

360 kg
-40° C - +100° C
Length: 1,4 m
300 g
360 kg
-40° C to +100° C
1.4 m
6 mm
0.3 kg
_

#### EUROLITE Steel rope 1400x6mm silver without quick link

Maximum load WLL (5-fold):	360 kg
Temperature range:	-40° C - +100° C
Dimensions:	Length: 1,4 m
Maximum load WLL (5-fold):	360 kg
Temperature range:	-40° C to +100° C
Rope length:	1.4 m
Rope diameter:	6 mm

#### EUROLITE Quick Link Type A-200

200 kg
DIN 56927:2009-03,
A - small opening
Steel, zinc-plated
0-7,5 mm
Length: 4,50 cm
Width: 5,80 cm
Depth: 2,70 cm
Diameter: Ø 6 mm
30 g