

REUTLINGER Cable glider type 80SVII-RM20 bk

Cable glider, up to 330 kg work load

Art. No.: 58010582

GTIN: 4026397400434



The article is no longer in our assortment.

Description:

Certified cable holder

Cable holders can be used for easily suspending static workloads on attachment ropes. No tools are required. The load can be hung at any position and height and easily be re-positioned.

The REUTLINGER cable holders are the only system certified by two independent certification bodies. This cable holder boasts of a TÜV certificate and a German BGV C1 certificate and can be used in entertainment technology.

TÜV GS and BGV C1 - double-tested and double-certified

REUTLINGER® grippers type 50 SV II, type 66 and type 80 SV II are not only certified as safe (GS) by the German TÜV, they have also been licensed for use within the scope of standard DGUV Regulation 17 (BGV C1).

The DGUV Test certificate authorises these grippers for use within the scope of the accident prevention regulations issued by the German employers' liability insurance associations in respect of staging and production facilities.

The test seal of the DGUV is conferred only after extensive examining of all load applications.

Further testing simulated most anticipated mis-applications.

REUTLINGER® gripper ranges 50, 66 and 80 are the only load-bearing devices certified by the DGUV for use in mobile production facilities.

Features:

- For rope diameters 6.0 to 8.0 mm
- 6-ball mechanism
- With eyering DIN 582 M20 black zinc plated C15E
- TÜV-GS
- German BG certificate

Logistic

EAN / GTIN: 4026397400434

Weight: 0,82 kg

Length: 0.15 m

Width: 0.11 m

Height: 0.04 m

- Please note: Cable gliders must not be used for dynamic loads. Always use at least 2 cable gliders for every suspended object.
- For further information about this product, please refer to the Data Sheet under "Downloads"

Technical specifications:

Work load:	8 mm: 330 kg 6 mm: 190 kg
Ring diameter:	Outside: 72 mm Inside: 40 mm
Dimensions:	Length: 15,50 cm
Weight:	820 g
Workload 6 mm:	190 kg
Workload 8 mm:	330 kg
Diameter:	40 mm
Thread:	M20
Thread length:	30 mm
Ring outer diameter:	72 mm
Ring inner diameter:	40 mm
Length:	155 mm