

SHZ Roundsling with Steel Inlay 0.5m/4000KG

Roundsling with steel inlay

Art. No.: 58010743 GTIN: 4026397471489







The article is no longer in our assortment.

Features:

- Steelflex with window complies with BGV C1
- For attaching loads
- Made from polyester, complies with DIN EN 1492-2
- Single-coated, thermically fix
- Printed load capacity
- No danger of injury for the hands
- Smooth transport of goods
- Highly flexible
- UV resistant
- Complies with EN 1492-2
- The useful length is 0,5 m

Technical specifications:

Max. load WLL (7-fold):	4000 kg
Standard:	EN 1492-2,
Color:	Black
Temperature range:	-40° C - +100° C
Useable length:	0,5 m
Weight:	0,55 kg

Logistic

EAN / GTIN: 4026397471489 Weight: 0,55 kg Length: 0.36 m Width: 0.36 m Heigth: 0.05 m

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.