

BLOCK AND BLOCK SIGMA-70 Truss lifter 160kg 5.3m

High-quality truss lift for loads up to 160 kg, made in EU

Art. No.: 59000410 GTIN: 4026397644180





List price: 1605.31 €

incl. 19% VAT.

Features:

- Four-part telescopic ground support
- Safety bolts to lock the different sections at different heights
- Locking bolts in the base area to lock the booms
- Booms with adjustable spindle and steel plate with non-slip rubber base
- Corrosion protection through epoxy coating
- Water level to ensure a vertical position
- Earthing connection
- Transport rolls to move the lift when retracted
- AL-KO 351 PLUS winch: Maximum load 350 kg with automatic holding brake. CE declaration of conformity in compliance with the harmonized standards DIN EN 13157, EN 12100 I and II, EC Machinery Directive 2006/42/CE
- Galvanized steel ropes 6x19+1, manufactured in compliance with the standard 13414-1:2004, tensile strength 1770N/mm2
- Material: Carbon steel S-275-J0H, manufactured in compliance with the standards EN10219 and EN10305.5
- Adjustable height
- Made in Europe
- With BGV-C1 test certificate

Technical specifications:

Maximum carrying capacity:	160 kg
Minimum load:	25 kg
Nominal tensile strenght of rope:	1770 N/mm²

Logistic

EAN / GTIN: 4026397644180 Weight: 46,00 kg Length: 0.36 m Width: 0.38 m Heigth: 1.75 m Bulky product

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo. Height: Maximum: 530 cm above 4 sections Minimum: 170 cm Ø 35mm Attachment system: Steel rope: Ø4mm Truss lifter Type (general stands): Material: Steel (powder-coated) Transport dimensions: 175 cm x 36 cm x 38 cm Base area: Ø 207 cm Weight: 43,50 kg