

## EUROLITE STC-300 Lighting stand

High-quality winch-stand

Art. No.: 59007003

GTIN: 4026397202670



The article is no longer in our assortment.

### Features:

- Made of steel
- 1-gear winch for easy lifting of the loads
- Automatic braking system
- Safety-pins for mechanic locking
- Ideal for mobile, professional lighting-systems or PA-systems
- Easy handling
- Complies with DIN 15560-27 and DIN EN ISO 12100-2
- Adjustable height
- TV spigot

### Logistic

EAN / GTIN: 4026397202670

Weight: 12,40 kg

Length: 1.48 m

Width: 0.18 m

Height: 0.14 m

Bulky product

### Technical specifications:

|                            |   |
|----------------------------|---|
| Maximum carrying capacity: | 35 kg   |
| Minimum load:              | 25 kg   |
| Standard:                  | DIN 15560-27, DIN EN ISO 12100-2                    |
| Height:                    | Maximum: 340 cm above 2 sections<br>Minimum: 150 cm |
| Attachment system:         | TV spigot Ø 28mm                                    |
| Steel rope:                | Ø 3 mm  |
| Type (general stands):     | Light stand/wind up                                 |
| Transport dimensions:      | 1,47 m x 18 cm x 14 cm                              |

|                       |                                  |
|-----------------------|----------------------------------|
| Base area:            | Ø 1,2 m                          |
| Weight:               | 11,65 kg                         |
| Type:                 | Winch-driven stand               |
| Construction:         | DIN 15560-27, DIN EN ISO 12100-2 |
| Certified by:         | CE                               |
| Sections:             | 2                                |
| Maximum load:         | 35 kg                            |
| Minimum load:         | 25 kg                            |
| Maximum height:       | 2.40 m                           |
| Minimum height:       | 1.50 m                           |
| Adapter: TV-Cone      | D:30 mm                          |
| Base area:            | D = 1.20 m                       |
| Transport dimensions: | 1.47 x 0.18 x 0.14 m             |