# ALUTRUSS SINGLELOCK SP-500 QUICK-LOCK Pipe

Single tube with quick-lock

**Art. No.: 60210010**

GTIN: 4026397187090

## List price: 53.43 €

incl. 19% VAT.

### Description:

SINGLELOCK SP 1-point truss system
SINGLELOCK SP is a 1-point truss system made of aluminum. The individual elements are connected via one cone, pivots and pins.

The advantage of the conical connection system is that the cone completely fits into the main chord so that highest load capacity is guaranteed. The Quick-Lock system enables fast, efficient and highly aesthetic assembly when the truss constructions are frequently assembled and dismantled.

The main chord is made of 50 mm aluminum tube with 2 mm wall thickness and offers a good relation between strength and weight.

SINGLELOCK SP is a stable truss system for higher loads and extended durability. This system is mainly designed for intense use in stage installations, fair installations, event installations but also for permanent installations in discotheques and theatres.

With SINGLELOCK SP, decorative frames with advertising signs, transmission canvas etc. can be realized.

The documentation of this truss system is closely related to the Codes of Practice SQ P1 - Truss Systems published by the VPLT/PLASA. The load table as calculation base can be downloaded from the Internet before buying the product!

### Logistic

EAN / GTIN: 4026397187090
Weight: 0,75 kg
Length: 0.57 m
Width: 0.06 m
Heigth: 0.06 m

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn
All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.

## Features:

- Low weight
- For decoration or frame construction for projection foils
- Easy installation
- Trusspipe: 50 mm
- Made in Europe
- For application areas such as: Shop fitting; Rental
- For further information about this product, please refer to the Data Sheet under "Downloads"
  **Package contents**
- 1 x connection Set

## Technical specifications:

| | |
|---|---|
| Setup: | Easy installation |
| Trusspipe: | 50 mm x 2 mm |
| Welding technique: | TIG-welding |
| Welding material: | AlMg 5 |
| Color: | Alu colored |
| Dimensions: | Length: 50 cm |
| Weight: | 720 g |

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn
All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.