alutruss

ALUTRUSS QUADLOCK S6082-5000 4-way Cross Beam

4-point truss system







List price: 1034.11 €

incl. 19% VAT.

Features:

- Strong EN-AW 6082 alloy for high loads
- High-quality aluminum-tubes with 50 mm in diameter
- Low weight
- Distance center center: 240 mm
- Easy installation
- Trusspipe: 50 mm
- TÜV Süd certified
- For application areas such as: Theater; Trade fair and shop fitting; clubs/dancing school **Package contents**
- 1 x connection set

Technical specifications:

Setup:	Easy installation
Trusspipe:	50 mm x 2 mm
Welding technique:	TIG-welding
Welding material:	AIMg 5
Alloy:	AIMgSi1 T6
Color:	Black
Strut diameter x thickness:	16 x 2mm
Dimensions:	Length: 500 cm

Logistic

EAN / GTIN: 4026397644067 Weight: 28,80 kg Length: 5.00 m Width: 0.29 m Heigth: 0.29 m Bulky product

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo. Width: 29 cm Height: 29 cm

Weight:

24,80 kg